

Thermakraft™

Thermakraft

FREEMPHONE: 0800 500 595
WEBSITE: www.thermakraft.co.nz

**ALUBAND™
WINDOW
WRAP**
WINDOW SEALING SYSTEM

Thermakraft

FREEMPHONE: 0800 500 595
WEBSITE: www.thermakraft.co.nz

**Water Vapour
Permeable**

Product Data Sheet

ALUBAND

Bituminous window flashing tape.

Aluband is designed specifically as a premium window flashing tape. Made with a heavy bituminous adhesive the product provides high strength bond and excellent abrasion resistance.

Aluband comes in four roll sizes:

Product Code	Roll Size	Rolls Per Carton
ALU075025	75mm x 25m	12
ALU150010	150mm x 10m	6
ALU150025	150mm x 25m	6
ALU200025	200mm x 25m	4

Smarter products. Better buildings.
thermakraft.com.au



Aluband

Bituminous adhesive flexible window flashing tape.

Scope of Use

Thermakraft Aluband Window Flashing Tapes can be used within the following scope:

- Installed into and around frame joinery opening over the wall membrane and exposed frame to cover both the face and edge of the opening framing as a secondary weather resistant barrier.
- Installed at joinery heads to seal flashing upstands to the wall membrane.
- To assist the overall weathertightness performance of window and door joinery installations.
- To be used in conjunction with air seals and joinery flashing systems. Installer must check for air seal product compatibility with Aluband Window Flashing Tape (for example, construction sealants and expanding foam).
- Thermakraft Aluband Window Flashing Tape must be used with Thermakraft Corner Moulded Pieces (on windowsill corners)
- Situated in non-cyclonic wind zones up to, and including N3.

General

- Compatible with Thermakraft building membrane.
- Unaffected by LOSP or other solvent based treated timber. However, LOSP or other solvent based treated timber must have sufficient time for the solvent chemical to flash off in well ventilated area. Recommended minimum 7days.
- Thermakraft corner moulds MUST be used at flashing corners (see installation guide)

Limitations

- Must NOT be exposed to the weather/UV for more than 42 days
- Should be installed when temperatures are above 5°C
- NOT designed to overcome poor detailing and workmanship of the window or door joinery installation
- Bitumen may react with window sealants. Always check compatibility before use.

Durability:

Aluband Window Flashing Tape is expected to have a serviceable life equal to that of the wall cladding provided:

- It is not damaged.
- Installed in accordance with installation guide.
- Is not left exposed to the weather or UV for more than 42 days.
- Is compatible with wall cladding system and construction sealants; foam or air seals products used**.

** Specifiers and product user must test for wall cladding system and construction sealants; foam or air seals products' compatibility with Aluband Window Flashing Tape before installation.

Product Warranty

For advice or information regarding Thermakraft products refer to Thermakraft literature or contact **1800 960 338**, visit **thermakraft.com.au** or follow the **QR code**.

Thermakraft Australia Pty Limited / 1800 960 338

Smarter products. Better buildings.
thermakraft.com.au

