



Timbermate[®]
group

Earl's Wood Hardener[®]

Rotten Wood Repairer

Restores timber like new



Ready to use straight from the container



No wastage



Non Toxic when cured



Volatile Organic Compound free



Saves costly replacement

Restores timber like new Save on costly replacements

Earl's[®] Wood Hardener penetrates into soft rotted wood fibres, restoring them to near original strength. This means you can repair even the most damaged wood, ready for full restoration.

No longer do you need to dig out the rot. Simply apply and Earl's Wood Hardener will penetrate. Once dry, patch and paint (if desired). It's as easy as 1-2-3!



Use Earl's Wood Hardener on

- Fences
- Weatherboards
- Window sill/sashes
- Playground equipment
- Door Frames
- Posts
- Panelling
- Fence Palings
- Furniture
- Outdoor tables/chairs
- Decorative beams
- Decks and more

Before & after



Before



After

Area shown has been treated with Earl's Wood Hardener and then filled with Earl's Powder Putty and painted.
Can use MulTfill or Porion as well.

Earl's Wood Hardener features

Ideal for interior and exterior jobs

Furniture, fences, decking, posts, window sills and sashes any wooden surface - the list is endless. Earl's Wood Hardener will save you hundreds of dollars on replacements.

Pre-mixed and ready to apply

Earl's Wood Hardener comes pre-mixed and ready to apply. Shake before use

Water based - safe and friendly

Modern technology has allowed the development of a water-based consolidant that is also non-toxic once cured and completely safe to use around the home and playgrounds etc.

Long shelf life

Earl's Wood Hardener has a shelf life in excess of two years. Always use in temperatures above 7°C.

Easy to Apply

Ensure area to be treated is dry, free of dirt, dust or grease and remove loose paint, varnish or flaky wood. Generously apply Earl's Wood Hardener by pouring, spraying, brushing or sponging onto area to be restored. Repeatedly saturate the rotted wood fibres to enable the deepest possible penetration. Let cure until solid and not tacky to the touch. Multiple treatments might be needed on extremely soft wood.

Earl's Wood Hardener should be considered a non-structural wood hardener. For more safety information, please read directions and safety instructions on the product's label before use. Tips for application: Find a spot 75mm (3") on either side of the rot, drill holes between these 2 points and spray, brush or syringe Earl's Wood Hardener into area.

Product code & barcode numbers

Product Code	Size	Pack Size	Barcode
EW25	250ml	12	931528430145
EW1	1 Litre	6	931528430169
EW4	4 Litre	1	931528430176

Note: The worse the rot, the more applications. In most instances only one or two coats are required. After 24 hours use fingernail to test if wood is still soft or adequately restored.

