

# Landscape SpecRite™

Manufactured For Results.



## MERBAU GARDEN EDGING

SELECT GRADE HARDWOOD-KILN DRIED-AS2796.2 2006



Available at

**BUNNINGS**  
warehouse

- Timber certified from legally verified forest sources
- Approved for use in bushfire-prone areas, compliant to BAL29
- Select Grade, Kiln-dried timber for stability and a high-quality clean appearance
- Durable for in-ground use
- Naturally resistant to fungi and insects like termites and dry wood borers



Australian Standard  
Compliant AS/NZS 2796



Kiln Dried  
Timber



Class A Bond Glue  
(Weather Resistant)



Select  
Grade

# MERBAU GARDEN EDGING

SELECT GRADE HARDWOOD-KILN DRIED-AS2796.2 2006

## Size & Length

69 mm x 7 mm, available in 5.7 metre lengths

## Installation / Use

For use as garden edging or screening, SpecRite Merbau Garden Edging is not designed to be freestanding or used in a structural or load-bearing situation. It is the sole responsibility of the homeowner, contractor or installer to determine the specific requirements, suitability and safety in regard to an application or use of this product. Merbau Garden Edging is not designed to be excessively bent in use. Please exercise caution as bending may cause breakage and injury.

## Fixings

Garden edging should be fixed using hot dipped galvanised or stainless steel screws for the best possible finish. Use timber, plastic or metal garden edging stakes to hold in position.

## Cutting

Tungsten carbide tipped cutting tools and high quality drill bits are recommended for best results. Apply timber oil to cut ends to maximise the life of the timber. Ensure appropriate eye, ear and breathing protection is used when cutting timber.

## Weathering and Finishing

Timber will naturally go grey if left unfinished. Merbau has tannin, a naturally occurring substance in timber which will leach the first few times it is exposed to water. It will stain timber, paved areas and concrete which is light in colour. Objects left on the timber surface will also draw tannin out, creating surface marks. A thorough and regular hose down during the first few days will assist with flushing excess tannin away. To prolong the life of Specrite Merbau Garden Edging and maintain its premium look, clean all surfaces using a stiff bristle brush and apply a minimum of 2 coats of timber oil containing a UV stabiliser, within 2 weeks of installation.

## Storage

Specrite Merbau Garden Edging should be stored flat, off the ground and protected from the weather prior to installation.



Item no.9931207  
Made in Indonesia

Available at  
**BUNNINGS**  
warehouse