# SAFETY DATA SHEET

Date of issue/Date of revision 14 December 2020

Version 2.05



### **Section 1. Identification**

Product code : 483120/4L

Product identifier : JOHNSTONES PROFESSIONAL WATER BASED INTERIOR FLOOR SATIN

#### Recommended use and restrictions

Use of the substance/

mixture

: Coating.

**Uses advised against** 

: Not applicable.

Supplier's details

: PPG Architectural Coatings

9 Birmingham Ave Villawood, NSW 2163

Australia

Tel: +61 2 9794 1200 Fax: + 61 2 9794 1237

**Emergency telephone** 

number

: Australia 1800 883 254 / New Zealand 0800 000 096

# Section 2. Hazard(s) identification

Classification of the

substance or mixture

: Not classified.

**GHS** label elements

Signal word : No signal word.

Hazard statements : No known significant effects or critical hazards.

**Precautionary statements** 

Prevention : Not applicable.

Response : Not applicable.

Storage : Not applicable.

Disposal : Not applicable.

Supplemental label : Not applicable.

elements

: Prolonged or repeated contact may dry skin and cause irritation. Contains

result in classification isothiazolinones. May cause allergic reaction.

## Section 3. Composition and ingredient information

Substance/mixture : Mixture

**CAS** number/other identifiers

Other hazards which do not

**CAS number** : Not applicable. **EC number** : Mixture.

Australia GHS Page: 1/10

Product code 483120/4L Date of issue 14 December 2020 Version 2.05

**Product name JOHNSTONES PROFESSIONAL WATER BASED INTERIOR FLOOR SATIN** 

### Section 3. Composition and ingredient information

Ingredient name	CAS number	% (w/w)
(2-methoxymethylethoxy)propanol propane-1,2-diol 2-(2-butoxyethoxy)ethanol	34590-94-8 57-55-6 112-34-5	1 - <10 1 - <10 1 - <10

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment or have an OEL and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

### Section 4. First aid measures

### **Description of necessary first aid measures**

**Eye contact**: Remove contact lenses, irrigate copiously with clean, fresh water, holding the

eyelids apart for at least 10 minutes and seek immediate medical advice.

**Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is

irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by

trained personnel.

**Skin contact**: Remove contaminated clothing and shoes. Wash skin thoroughly with soap and

water or use recognised skin cleanser. Do NOT use solvents or thinners.

**Ingestion** : If swallowed, seek medical advice immediately and show the container or label.

Keep person warm and at rest. Do NOT induce vomiting.

#### Most important symptoms/effects, acute and delayed

#### Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.
 No known significant effects or critical hazards.

### Over-exposure signs/symptoms

Eye contact : No specific data.

Inhalation : No specific data.

Skin contact : No specific data.

Ingestion : No specific data.

### Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician : Treat symptomatically. Contact poison treatment specialist immediately if large

quantities have been ingested or inhaled.

**Specific treatments**: No specific treatment.

Protection of first-aiders : No action shall be taken involving any personal risk or without suitable training.

See toxicological information (Section 11)

Australia GHS Page: 2/10

Date of issue 14 December 2020 Version 2.05

Product name JOHNSTONES PROFESSIONAL WATER BASED INTERIOR FLOOR SATIN

### Section 5. Firefighting measures

#### **Extinguishing media**

Suitable extinguishing

media

Unsuitable extinguishing media

: None known.

Specific hazards arising

from the chemical

: In a fire or if heated, a pressure increase will occur and the container may burst.

**Hazardous thermal** decomposition products : Decomposition products may include the following materials: carbon oxides metal oxide/oxides

: Use an extinguishing agent suitable for the surrounding fire.

Special protective actions for fire-fighters

Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without

**Special protective** equipment for fire-fighters : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

Hazchem code : Not applicable.

# Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.

For emergency responders

: If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** 

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

#### Methods and material for containment and cleaning up

**Small spill** 

: Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

Large spill

: Stop leak if without risk. Move containers from spill area. Prevent entry into sewers. water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with noncombustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for emergency contact information and Section 13 for waste disposal.

> **Australia GHS** Page: 3/10

Date of issue 14 December 2020 Version 2.05

Product name JOHNSTONES PROFESSIONAL WATER BASED INTERIOR FLOOR SATIN

### Section 7. Handling and storage

#### Precautions for safe handling

**Protective measures** 

: Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas.

Advice on general occupational hygiene Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.

including any incompatibilities

Conditions for safe storage, : Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

### Section 8. Exposure controls and personal protection

#### **Control parameters**

#### **Occupational exposure limits**

(2-methoxymethylethoxy)propanol

propane-1,2-diol

2-(2-butoxyethoxy)ethanol

Safe Work Australia (Australia, 12/2019). Absorbed through skin.

TWA: 308 mg/m<sup>3</sup> 8 hours. TWA: 50 ppm 8 hours.

Safe Work Australia (Australia, 12/2019).

TWA: 10 mg/m<sup>3</sup> 8 hours. Form: Particulate TWA: 474 mg/m<sup>3</sup> 8 hours. Form: Vapor

and particulates

TWA: 150 ppm 8 hours. Form: Vapor and

particulates

ACGIH TLV (United States, 3/2019).

TWA: 10 ppm 8 hours. Form: Inhalable

fraction and vapor

#### **Appropriate engineering** controls

: Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

For products that are sprayed, where practicable use a spray booth designed and maintained in accordance with AS/ NZS 4114.

#### **Environmental exposure** controls

: Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

#### **Individual protection measures**

**Australia GHS** Page: 4/10

Date of issue 14 December 2020 Version 2.05

**Product name JOHNSTONES PROFESSIONAL WATER BASED INTERIOR FLOOR SATIN** 

### Section 8. Exposure controls and personal protection

**Hygiene measures** 

Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

**Eye/face protection** 

**Hand protection** 

**Skin protection** 

: Safety glasses with side shields.

: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates

this is necessary.

**Gloves** : For prolonged or repeated handling, use the following type of gloves:

Recommended: Viton®, butyl rubber, nitrile rubber

**Body protection**: Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist

before handling this product.

Other skin protection : Appropriate footwear and any additional skin protection measures should be

selected based on the task being performed and the risks involved and should be

approved by a specialist before handling this product.

**Respiratory protection**: Respirator selection must be based on known or anticipated exposure levels, the

hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is

necessary.

Restrictions on use : Not applicable.

References: Eye protectors should conform to AS/NZS 1336 and AS/NZS 1337. Chemical-resistant gloves should conform to AS/NZS 2161.1. Respiratory protection should conform to AS/NZS 1715 and AS/NZS 1716. Occupational footwear should conform to AS/NZS 2210.

### Section 9. Physical and chemical properties

**Appearance** 

Physical state : Liquid.
Colour : Clear.

Odour : Not available.
Odour threshold : Not available.

pH : 9

Melting point : Not available.

Boiling point : ▶37.78°C (>100°F)

Flash point : Closed cup: 100°C (212°F) [Product does not sustain combustion.]

Evaporation rate : Not available.
Flammability (solid, gas) : Not available.
Lower and upper explosive : Not available.

(flammable) limits

Vapour pressure: Not available.Vapour density: Not available.

Relative density : 1.04
Bulk Density (g/cm³) : 1.03

Australia GHS Page: 5/10

Product code 483120/4L Date of issue 14 December 2020 Version 2.05

**Product name JOHNSTONES PROFESSIONAL WATER BASED INTERIOR FLOOR SATIN** 

### Section 9. Physical and chemical properties

**Solubility**: Partially soluble in the following materials: cold water.

: Not available.

Partition coefficient: n-

octanol/water

Auto-ignition temperature : Not available.

Decomposition temperature : Not available.

Viscosity : Not Applicable

### Section 10. Stability and reactivity

**Reactivity**: No specific test data related to reactivity available for this product or its ingredients.

**Chemical stability** : The product is stable.

Possibility of hazardous reactions

: Under normal conditions of storage and use, hazardous reactions will not occur.

**Conditions to avoid** : Stable under recommended storage and handling conditions (see Section 7). When exposed to high temperatures may produce hazardous decomposition products.

Incompatible materials
 Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

Hazardous decomposition products

: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides

### **Section 11. Toxicological information**

### Information on toxicological effects

### **Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
(2-methoxymethylethoxy) propanol	LC50 Inhalation Vapour	Rat	500 ppm	4 hours
	LD50 Dermal	Rabbit	9.5 g/kg	-
	LD50 Oral	Rat	5.23 g/kg	-
propane-1,2-diol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
, , , , , , , , , , , , , , , , , , , ,	LD50 Oral	Rat	4500 mg/kg	-

Conclusion/Summary Irritation/Corrosion : There are no data available on the mixture itself.

Not available.

**Conclusion/Summary** 

Skin: There are no data available on the mixture itself.Eyes: There are no data available on the mixture itself.Respiratory: There are no data available on the mixture itself.

**Sensitisation** 

Not available.

**Conclusion/Summary** 

**Skin**: There are no data available on the mixture itself.

Australia GHS Page: 6/10

Product code 483120/4L Date of issue 14 December 2020 Version 2.05

**Product name JOHNSTONES PROFESSIONAL WATER BASED INTERIOR FLOOR SATIN** 

### Section 11. Toxicological information

Respiratory

: There are no data available on the mixture itself.

**Mutagenicity** 

Not available.

**Conclusion/Summary** 

: There are no data available on the mixture itself.

Carcinogenicity

Not available.

Conclusion/Summary :

: There are no data available on the mixture itself.

Reproductive toxicity

Not available.

**Conclusion/Summary** 

: There are no data available on the mixture itself.

**Teratogenicity** 

Not available.

**Conclusion/Summary**: There are no data available on the mixture itself.

Specific target organ toxicity (single exposure)

Not available.

Specific target organ toxicity (repeated exposure)

Not available.

**Aspiration hazard** 

Not available.

Information on likely routes

of exposure

: Not available.

Potential acute health effects

Eye contact
 Inhalation
 No known significant effects or critical hazards.
 Skin contact
 No known significant effects or critical hazards.
 Ingestion
 No known significant effects or critical hazards.

#### Symptoms related to the physical, chemical and toxicological characteristics

Eye contact : No specific data.
Inhalation : No specific data.
Skin contact : No specific data.
Ingestion : No specific data.

#### Delayed and immediate effects as well as chronic effects from short and long-term exposure

**Conclusion/Summary** 

There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater

Australia GHS Page: 7/10

### **Section 11. Toxicological information**

hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long-term exposure by oral, inhalation and dermal routes of exposure and eye contact.

**Short term exposure** 

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects

: There are no data available on the mixture itself.

**Long term exposure** 

**Potential immediate** 

effects

: There are no data available on the mixture itself.

Potential delayed effects : There are no data available on the mixture itself.

Potential chronic health effects

Not available.

General : No known significant effects or critical hazards.
 Carcinogenicity : No known significant effects or critical hazards.
 Mutagenicity : No known significant effects or critical hazards.
 Reproductive toxicity : No known significant effects or critical hazards.

#### **Numerical measures of toxicity**

#### **Acute toxicity estimates**

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	,	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
MOHNSTONES PROFESSIONAL WATER BASED INTERIOR FLOOR SATIN	N/A	104751.8	N/A	1304	N/A
(2-methoxymethylethoxy)propanol	5230	9500	N/A	N/A	N/A
propane-1,2-diol	20000	20800	N/A	N/A	N/A
2-(2-butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A

### **Section 12. Ecological information**

#### **Toxicity**

Product/ingredient name	Result	Species	Exposure
(2-methoxymethylethoxy) propanol	Acute EC50 1919 mg/l	Daphnia	48 hours
1	Acute LC50 40613 mg/l	Fish	96 hours

#### Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
propane-1,2-diol	-	-	Readily

#### **Bioaccumulative potential**

Date of issue 14 December 2020 Version 2.05

**Product name JOHNSTONES PROFESSIONAL WATER BASED INTERIOR FLOOR SATIN** 

### Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
propane-1,2-diol	-0.92	-	low
2-(2-butoxyethoxy)ethanol	0.56	-	low

**Mobility in soil** 

Soil/water partition coefficient (Koc)

: Not available.

Other adverse effects : No

: No known significant effects or critical hazards.

### Section 13. Disposal considerations

**Disposal methods** 

: The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

### **Section 14. Transport information**

	ADG	IMDG	IATA
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

#### **Additional information**

ADG : None identified.

Hazchem code : Not applicable.

IMDG : None identified.

IATA : None identified.

Australia GHS Page: 9/10

Date of issue 14 December 2020 Version 2.05

**Product name JOHNSTONES PROFESSIONAL WATER BASED INTERIOR FLOOR SATIN** 

### **Section 14. Transport information**

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according: Not applicable.

to IMO instruments

# Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons

**SUSMP** : Not regulated.

Model Work Health and Safety Regulations - Scheduled Substances

No listed substance

Australia inventory (AICS) : All components are listed or exempted. New Zealand (NZIoC) : All components are listed or exempted.

### Section 16. Any other relevant information

**History** 

Date of issue/Date of

revision

Date of previous issue

: 11/3/2020

: 14 December 2020

Prepared by

: EHS

Key to abbreviations

: ADG = Australian Dangerous Goods ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships,

1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) NOHSC = National Occupational Health and Safety Commission SUSMP = Standard Uniform Schedule of Medicine and Poisons

UN = United Nations

: Not available. References

Indicates information that has changed from previously issued version.

#### **Notice to reader**

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.

> **Australia GHS** Page: 10/10