

# SurePave™

## Permeable Paving Panels

TECHNICAL DATA SHEET	TDS G 001 003
ISSUE NUMBER	03
DATE	SEPTEMBER 2019

<b>STRUCTURE</b>	Interlocking Open Structure Hollow Pavers
<b>LOCKING SYSTEM</b>	Positive Lock Clipping System
<b>PANEL DIMENSIONS</b>	816mm x 612mm x 40mm
<b>MATERIAL</b>	Polypropylene Recycled
<b>UNIT WEIGHT</b>	2kg
<b>CRUSH STRENGTH UNFILLED</b>	>133 tonnes/m <sup>2</sup>
<b>CRUSH STRENGTH FILLED WITH STONE</b>	>740 tonnes/m <sup>2</sup>
<b>TEST METHODS</b>	Compression, NZS 3116 : 1991, App A & B
<b>MAXIMUM RECOMMENDED GRADIENT</b>	≤ 11 degrees



ISO 9001:2015  
 Registration number: C41186

The listed technical values are guiding values, achieved in our laboratories and/or independent testing institutes. Our products are subject to changes without prior notice.

#### DISCLAIMER

The information provided in this publication is correct to the best knowledge of the company and is given out in good faith. The information presented herein is intended only as a general guide to the use of such products and no liability is accepted by Cirtex Industries Ltd for any loss or damage however arising, which results either directly or indirectly from the use of such information. Cirtex Industries Ltd has a policy of continuous development so information and product specifications may change without notice.