

Meets your requirements: Case: robust, large, stable and secure with lid brake. Lowers your costs: The right tool protects you from damaging materials and avoids subsequent work. Increases your safety: Internationally award-winning VDE-insulated tools, each individually tested at 10,000 V AC and approved for use at 1,000 V AC. Gas-filled shock absorbers hold the lid in all positions and reduce the risk of injury when closing. Protects your health: Wiha pliers require less force and reduce pressure on wrists. Ergonomic handle design makes work easier and prevents occupational illnesses. Carry belt enables the simple transport of the tool case and keeps hands free for other materials. Increases your efficiency: A comprehensive tool assortment, always having the right tool at hand when needed. The design and function of the tool trays guarantee quick and easy access to tools. Increases your flexibility: Ample space for additional tools and lots of storage for small parts and machines.

Assorted case 80-pcs.

Assorted case 80-pcs.	
Order-No.	
10523	1
rimmin	g/cutting
K	Professional BiCut® high-performance diagonal cutters with DynamicJoint® switchable, Tool tested at 10,000 V AC / 200 mm, 8" (38191)
K	Diagonal cutters Professional electric with DynamicJoint®, Tool tested at 10,000 V AC / 180 mm, 7" (26744)
<u> </u>	Precision mechanic's diagonal cutters Classic with opening spring 125 mm, 5" (36189)
Stripping	g/skinning/crimping
<u> </u>	Installation pliers TriCut Professional electric, Tool tested at 10,000 V AC / 170 mm, 7" (38552)
	Stripping tool automatic up to 6 mm ² in blister pack 190 mm, 7½" (36050)
	Stripping tool with self-rotating trailing blade 165 mm, 6½" (35969)
	Crimp tool for wire-end sleeves 220 mm, 0,14-10 mm² (33844)
Supplyin	g/holding
	Water pump pliers Professional electric with push button adjustment, Tool tested at 10,000 V AC / 250 mm, 10" (37450)
•	Needle nose pliers Professional electric with cutting edge curved form, approx. 40°, Tool tested at 10,000 V AC / 200 mm, 8" (26729)
	Combination pliers Professional electric with DynamicJoint® and OptiGrip with extra long cutting edge, Tool tested at 10,000 V AC / 180 mm, 7" (26708)
•	Needle nose pliers Professional electric with cutting edge straight form, Tool tested at 10,000 V AC / 200 mm, 8" (26727)
	Folding what applife 0 or matrix 10 approach (07057)
	Folding ruler Longlife 2 m metric, 10 segments (27057)
	Switch cabinet spirit level (36859)
astenin	g/clamping
0	Screwdriver SoftFinish® electric Hex nut driver, Tool tested at 10,000 V AC / 5,5 x 125 (00856) / 7 x 125 (00858) / 8 x 125 (00859) / 10 x 125 (00861)
	Voltage tester Volt Detector non-contact, single-pole, 230-1,000 VAC (37871)
-	Voltage tester SoftFinish® single-pole, 110-250 volts (34745)
⊖	Screwdriver SoftFinish® electric slimFix Slotted, Tool tested at 10,000 V AC / 3,5 x 100 (35446) / 4,0 x 100 (35390) / 5,5 x 125 (35391) / 6,5 x 150 (35392)
Đ	Screwdriver SoftFinish® electric slimFix electric PlusMinus/Phillips, Tool tested at 10,000 V AC / SL/PH1 x 80 (35502) / SL/PH2 x 100 (35503)
₩	Screwdriver SoftFinish® electric slimFix PlusMinus/Pozidriv, Tool tested at 10,000 V AC / SL/PZ1 x 80 (36329) / SL/PZ2 x 100 (36330)
D	Screwdriver SoftFinish® electric slimFix Phillips, Tool tested at 10,000 V AC / PH1 x 80 (35393) / PH2 x 100 (35394)
\$	Screwdriver SoftFinish® electric slimFix Pozidriv, Tool tested at 10,000 V AC / PZ1 x 80 (35395) / PZ2 x 100 (35396)
\Rightarrow	Screwdriver SoftFinish® Slotted with one-piece hexagonal blade and solid steel cap 12,0 x 200 (03231)
⊕ ⊕ • • • • • • • • • • • • • • • • • •	
~ <i>*</i> *	Screwdriver with bit magazine LiftUp electric (38611)
⊕⊕⊛	1 x 3,0 /1 x 4,0 /1 x 5,5 /1 x PH1 /1 x PH2 /1 x SL/PZ2

 $\oplus \oplus \oplus \$ \quad 1 \times 4.5 / 1 \times 5.5 / 1 \times 6.5 / 2 \times PH1 / 4 \times PH2 / 1 \times PH3 / 2 \times PZ1 / 5 \times PZ2 / 1 \times PZ3 / 2 \times T10 / 2 \times T15 / 2 \times T20 / 3 \times T25 / 2 \times T30 / 1 \times T40 / 1 \times$

L-key set in Compact holder (01418) 1,5 / 2 / 2,5 / 3 / 4 / 5 / 6 / 8 / 10

/1 x Bit holder magnetic, 58 mm

Bit set XLSelector Standard 25 mm (29417)

