


EARTHWOOL® GLASSWOOL INSULATION: CEILING

November 2021



APPLICATIONS



DESCRIPTION

The Earthwool® glasswool insulation: ceiling batt range includes a selection of R-values to provide builders, designers, installers and DIYers the opportunity to choose the best thermal performance for their project. Earthwool® glasswool insulation: ceiling batt will improve the thermal comfort and energy efficiency of the building in which it has been installed thus keeping it cool in summer and warm in winter.

The super-soft and easy to handle benefits of Earthwool® glasswool have been further enhanced with TwinTech®. TwinTech® heralds another advancement in insulation manufacture - the dual forming technique ensures there is a smooth finish on both sides of the insulation, which improves product handling and appearance. Earthwool® glasswool insulation: ceiling batt is made using up to 80% recycled glass and with ECOSE® Technology, a sustainable, bio-based binder that contains no added formaldehyde.



Enhanced moisture resistance with DriTherm® technology. Earthwool® glasswool insulation is silicone treated, which provides moisture resistance for up to 50 years.

PERFORMANCE

Thermal	AS/NZS 4859.1 (2018).
Fire Hazard Properties (AS/NZ 1530.3)	Ignitability: 0, Spread of Flame: 0, Heat Evolved: 0, Smoke Developed: 0-1.
Water Vapour Absorption	Less than 5% by weight.
Microbial Growth	Does not support microbial growth.
Corrosion Resistance	No greater than sterile cotton.
Combustibility (AS 1530.1)	Non-combustible.


BENEFITS

- ✓ DriTherm® technology - silicone treated glasswool for increased durability
- ✓ TwinTech® - smooth finish on both sides
- ✓ High thermal performance - year round comfort
- ✓ Sound absorbing
- ✓ Non-combustible
- ✓ Saves energy - lower energy bills
- ✓ No added formaldehyde
- ✓ Soft to handle and install
- ✓ 50 year warranty
- ✓ Compression packed - more product per pack
- ✓ Odourless.

CERTIFICATION



Declare.



EARTHWOOL® GLASSWOOL INSULATION: CEILING

November 2021

SPECIFICATIONS

CEILING SEGMENTS

Product Code	R-Value (m ² K/W)	Thermal Conductivity (W/mK)	Thickness (mm)	Width (mm)	Length (mm)	Area per pack (m ²)	Pieces per pack
683642	3.2 SKILLION	0.033	105	430	1160	5.5	11
683674	3.3	0.047	155	430	1160	10.5	21
731850	3.6	0.049	175	430	1160	8.5	17
731848	3.6	0.049	175	600	1200	12.2	17
731846	4.1	0.048	195	430	1160	7.5	15
683653	5.2	0.040	210	430	1160	5.5	11
683654	6.3	0.044	275	430	1160	5.5	11

All dimensions are nominal.

EARTHWOOL® GLASSWOOL INSULATION: CEILING

November 2021

ADDITIONAL INFORMATION

Specification Guide

The ceiling insulation shall be Earthwool® glasswool insulation: ceiling batt * R*, *mm thick, BRANZ appraised to meet the provisions of the NZBC. The product will be non-combustible, Red List Free as labelled by Declare, Global GreenTag Level A certified, glasswool insulation with high post-consumer recycled glass content and with ECOSE® Technology. It will be manufactured under Quality Assurance Standards ISO 9001:2008 and ISO 14001:2004 by Knauf Insulation and shall be installed in accordance with the instructions issued by them.

*architect to insert details of products used.

Specification Compliance

AS/NZS 4859.1: 2018 Materials used in the Thermal Insulation of Buildings and comply with the New Zealand Building Code requirements: B2 – Durability, E3 – External Moisture, F2 – Hazardous Building Materials, and H1 – Energy Efficiency, as appraised by BRANZ. The Earthwool® glasswool insulation: ceiling batt range is an acceptable solution in terms of the New Zealand Building Code. This product is designed for use in timber and metal frame applications in new and existing domestic and commercial buildings.

Bio-solubility

The formulation used for Earthwool® glasswool insulation has been independently assessed to meet the requirements of the stringent Note Q standard (and is therefore consistent with the highest Australian and New Zealand industry standards), and also assessed by Knauf Insulation against NZ Work-Safe requirements. Earthwool® glasswool is classified as a non-hazardous substance in line with the NOHSC: 1008 3rd Edition.

Environmental

Earthwool® glasswool insulation: ceiling batt represents no known threat to the environment and comes with GreenTag Level A certification, Declare label and a certified Environmental Product Declaration. Earthwool® glasswool has low VOC and benefits from ECOSE® Technology.

Proven Performance

- Earthwool® glasswool insulation is preferred by professional installers concerned with quality, appearance and productivity.
- Earthwool® glasswool insulation has excellent acoustical properties reduce sound transmission in the home when properly installed in walls, ceiling and floor systems.

Durability

- Earthwool® glasswool insulation is odourless, rot proof, non-hygroscopic, does not sustain vermin and will not encourage the growth of fungi, mould or bacteria.
- DriTherm® technology - silicone treated for increased durability.

Superior Handling

- Highly resilient insulation recovers quickly to full thickness for a snug fit and superior finished aesthetics.
- Consistent quality materials feel good, cut easily and install fast.
- Low dust for easier handling and increased productivity.

Convenient Packaging, Easier Handling

- Earthwool® glasswool insulation is packaged in a strong, white poly bags (batts) and film (rolls) that offers excellent protection from abuse, dust and moisture.
- Earthwool® glasswool insulation packages feature easy to follow installation instructions.
- MasterBag insulation units (containing multiple packs) ensure reduced handling costs with improved compression – more square metres per bag, more square metres per truck load, fewer trips to the job site and less warehouse space for storage.

Superior Service and Support

- Knauf Insulation is focused on providing first class customer service, producing high quality products and 'in full on time' deliveries.
- Knauf Insulation recognises the need to establish, develop and support a professional network of distributors and re-sellers in order to service a growing insulation market.
- Knauf Insulation is committed to providing a comprehensive range of relevant sales and marketing literature and web-based technical information to support specifiers and customers.



Earthwool® glasswool products made with ECOSE® Technology benefit from a no added formaldehyde binder, which is less energy intensive than traditional binders and is based on rapidly renewable, bio-based materials instead of petro-based chemicals. The technology has been developed for Knauf Insulation's glass and rock mineral wool products, enhancing their environmental credentials without affecting the thermal, acoustic or fire performance. Earthwool® glasswool products made with ECOSE® Technology contain no added dyes or artificial colours.

Knauf Insulation Ltd

PO Box 217063, Botany Junction, Auckland, 2164, New Zealand

Customer Service: Tel: 0800 562 834

Technical Advisory Centre: tech.nz@knaufinsulation.com

All rights reserved, including those of photomechanical reproduction and storage in electronic media. Extreme caution was observed when putting together and processing the information, texts and illustrations in this document. Nevertheless, errors cannot quite be ruled out. The publisher and editors cannot assume legal responsibility or any liability whatever for incorrect information and the consequences thereof. The publisher and editors will be grateful for improvement suggestions and details of possible errors pointed out.

KINZ1213029DS [v0.3]

challenge.
create.
care.