

# 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	801-LINE BRITISH PAINTS SEMI GLOSS ENAMEL
Recommended Use:	Solvent based surface coating. Applied by brush, roller or spray.
Supplier: ABN: Street Address:	Dulux Australia, a division of DuluxGroup (Australia) Pty Ltd 67 000 049 427 1956 Dandenong Road, Clayton, Victoria Australia
Telephone Number: Facsimile: Emergency Telephone:	+61 3 9263 5678 +61 3 9263 5777 <b>1 800 033 111 (ALL HOURS)</b>

### 2. HAZARDS IDENTIFICATION

This material is hazardous according to criteria of Safe Work Australia; HAZARDOUS SUBSTANCE.

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.

Risk Phrases:Flammable. Irritating to skin.Safety Phrases:Keep away from sources of ignition - No Smoking. Avoid contact with skin. After<br/>contact with skin, wash immediately with plenty of water (or soap and water if product<br/>is water insoluble).

Poisons Schedule:

None allocated.

## **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Components	CAS Number	Proportion	Risk Phrases
Pigments	-	10-60%	-
Synthetic polymer(s)	-	10-60%	-
Mineral turpentine	-	10-60%	R10, R38, R65
White spirit (Stoddard solvent)	8052-41-3	10-60%	R65
Kerosine	8008-20-6	10-60%	R10, R38, R65
Solvent naphtha (petroleum), light arom.	64742-95-6	1-<10%	R65
Xylene	1330-20-7	1-<5%	R10 R20/21 R38
Ingredients determined not to be hazardous	-	to 100%	-

## 4. FIRST AID MEASURES

For advice, contact a Poisons Information Centre (e.g. phone Australia 131 126; New Zealand 0800 764 766) or a doctor.



### Inhalation:

Remove victim from area of exposure - avoid becoming a casualty. Remove contaminated clothing and loosen remaining clothing. Allow patient to assume most comfortable position and keep warm. Keep at rest until fully recovered. If patient finds breathing difficult and develops a bluish discolouration of the skin (which suggests a lack of oxygen in the blood - cyanosis), ensure airways are clear of any obstruction and have a qualified person give oxygen through a face mask. Apply artificial respiration if patient is not breathing. Seek immediate medical advice.

#### Skin Contact:

If skin or hair contact occurs, immediately remove any contaminated clothing and wash skin and hair thoroughly with running water. If swelling, redness, blistering or irritation occurs seek medical assistance.

### Eye Contact:

If in eyes, wash out immediately with water. In all cases of eye contamination it is a sensible precaution to seek medical advice.

### Ingestion:

If swallowed, do NOT induce vomiting. Give a glass of water. Get to a doctor or hospital quickly.

### Medical attention and special treatment:

Treat symptomatically.

### **5. FIRE FIGHTING MEASURES**

### Hazards from combustion products:

Flammable liquid. On burning will emit toxic fumes.

#### Precautions for fire fighters and special protective equipment:

Keep containers cool with water spray. Fire fighters to wear self-contained breathing apparatus and suitable protective clothing if risk of exposure to vapour or products of combustion.

#### Suitable Extinguishing Media:

Alcohol resistant foam is the preferred firefighting medium but, if it is not available, normal protein foam can be used.

#### Hazchem Code: · 3Y

### 6. ACCIDENTAL RELEASE MEASURES

### Emergency procedures:

If contamination of sewers or waterways has occurred advise local emergency services.

#### Methods and materials for containment and clean up:

SMALL SPILLS: Collect in a container for disposal via special chemical waste collection.

LARGE SPILLS: Shut off all possible sources of ignition. Wear protective equipment to prevent skin and eye contact. Avoid breathing in vapours. Work up wind or increase ventilation. Contain - prevent run off into drains and waterways. Use absorbent (soil, sand or other inert material). Collect and seal in properly labelled containers or drums for disposal.

## 7. HANDLING AND STORAGE

### Conditions for safe storage:

Store in a well ventilated area away from foodstuffs, oxidising agents and sources of heat or ignition. Keep containers closed when not in use - check regularly for leaks.

Product Name: 801-LINE BRITISH PAINTS SEMI GLOSS ENAMEL Substance No: 00000020137 Issued: 13/04/2010



### Precautions for safe handling:

Keep out of reach of children. Avoid skin and eye contact and breathing in vapour. All potential sources of ignition (open flames, pilot lights, furnaces, spark producing switches and electrical equipment etc) must be eliminated both in and near the work area. Do NOT smoke. Vapour may travel a considerable distance to source of ignition and flash back.

### 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

**Occupational Exposure Limits:** No value assigned for this specific material by the National Occupational Health and Safety Commission. However, Exposure Standard(s) for constituent(s):

Mineral turpentine: 8hr TWA = 480 mg/m<sup>3</sup> White spirits: 8hr TWA = 790 mg/m<sup>3</sup> Xylene (o-, m-, p- isomers): 8hr TWA = 350 mg/m<sup>3</sup> (80 ppm), 15 min STEL = 655 mg/m<sup>3</sup> (150 ppm)

As published by the National Occupational Health and Safety Commission.

No Exposure Standards assigned to other constituents.

TWA - The time-weighted average airborne concentration over an eight-hour working day, for a five-day working week over an entire working life.

STEL (Short Term Exposure Limit) - the average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight hour work day. According to current knowledge this concentration should neither impair the health of, nor cause undue discomfort to, nearly all workers.

These Exposure Standards are guides to be used in the control of occupational health hazards. All atmospheric contamination should be kept to as low a level as is workable. These exposure standards should not be used as fine dividing lines between safe and dangerous concentrations of chemicals. They are not a measure of relative toxicity.

### Engineering controls:

Provide adequate ventilation. If using indoors, keep windows and doors open during use. Keep containers closed when not in use.

### **Personal Protective Equipment:**

The selection of PPE is dependant on a detailed risk assessment. The risk assessment should consider the work situation, the physical form of the chemical, the handling methods, and environmental factors.

Personal Protection: G - OVERALLS, SAFETY SHOES, SAFETY GLASSES, GLOVES, RESPIRATOR.



Product Name: 801-LINE BRITISH PAINTS SEMI GLOSS ENAMEL Substance No: 00000020137 Issued: 13/04/2010



MANUFACTURE, PACKAGING AND TRANSPORT: Wear overalls, safety glasses and impervious gloves. Use with adequate ventilation. If inhalation risk exists wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS1716. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use.

FOR CONSUMER USE: Avoid contact with eyes and skin. Use with adequate ventilation. If risk of inhalation exists, wear organic vapour/particulate respirator meeting the requirements of AS/NZS 1715 and AS/NZS 1716.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Colour: Odour: Solubility: Specific Gravity: Relative Vapour Density (air=1): Vapour Pressure (20 °C): Flash Point (°C): Flammability Limits (%): Autoignition Temperature (°C): % Volatile by Volume: Solubility in water (g/L): Melting Point/Range (°C): Boiling Point/Range (°C): Decomposition Point (°C): nH:	Coloured Solvent Insoluble in water. Soluble in organic solvents. 0.9-1.4 @20°C >1 Not available >23 Not available Not available Not available Insoluble Not available Not available Not available Not available Not available Not available
рн: Viscosity: Evaporation Rate:	Not applicable Not available Not available
Vapour Pressure (20 °C): Flash Point (°C): Flammability Limits (%): Autoignition Temperature (°C): % Volatile by Volume: Solubility in water (g/L): Melting Point/Range (°C): Boiling Point/Range (°C): Decomposition Point (°C): pH: Viscosity:	>23 Not available Not available Not available Insoluble Not applicable Not available Not available Not available Not available

# **10. STABILITY AND REACTIVITY**

Chemical stability:	Stable under normal conditions of use.
Conditions to avoid:	Avoid contact with foodstuffs. Avoid exposure to heat, sources of ignition, and open flame. Avoid contact with oxidising agents.
Incompatible materials:	Incompatible with oxidising agents.
Hazardous decomposition products:	Oxides of carbon.
Hazardous reactions:	None known.

### 11. TOXICOLOGICAL INFORMATION

No adverse health effects expected if the product is handled in accordance with this Safety Data Sheet and the product label. Symptoms or effects that may arise if the product is mishandled and overexposure occurs are:

Product Name: 801-LINE BRITISH PAINTS SEMI GLOSS ENAMEL Substance No: 00000020137



Ingestion:	Swallowing can result in nausea, vomiting and central nervous system depression. If the victim is showing signs of central system depression (like those of drunkeness) there is greater likelihood of the patient breathing in vomit and causing damage to the lungs.
Eye contact:	May be an eye irritant.
Skin contact:	Contact with skin will result in irritation. Will have a degreasing action on the skin. Repeated or prolonged skin contact may lead to irritant contact dermatitis.
Inhalation:	Material may be irritant to the mucous membranes of the respiratory tract (airways). Breathing in vapour can result in headaches, dizziness, drowsiness, and possible nausea. Breathing in high concentrations can produce central nervous system depression, which can lead to loss of co-ordination, impaired judgement and if exposure is prolonged, unconsciousness.
Long Term Effects:	

No information available for the product.

Toxicological Data: No LD50 data available for the product.

### **12. ECOLOGICAL INFORMATION**

Ecotoxicity

Avoid contaminating waterways.

## **13. DISPOSAL CONSIDERATIONS**

### **Disposal methods:**

For large quantities: Refer to Waste Management Authority. Advise flammable nature. Dispose of material through a licensed waste contractor. Normally suitable for incineration by an approved agent.

For small quantities: Do not pour leftover paint down the drain. Unwanted paint should be brushed out on newspaper, allowed to dry and then disposed of via domestic waste collection. Empty paint containers should be left open in a well ventilated area to dry out. When dry recycle the container via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may differ between local authorities. Check with your local council first.

# 14. TRANSPORT INFORMATION

### Road and Rail Transport

Classified as Dangerous Goods by the criteria of the Australian Dangerous Goods Code (ADG Code) for Transport by Road and Rail; DANGEROUS GOODS.



UN No:1263Class-primary3 Flammable LiquidPacking Group:IIIProper Shipping Name:PAINTHazchem Code:· 3YProduct Name: 801-LINE BRITISH PAINTS SEMI GLOSSENAMELSubstance No: 00000020137

Issued: 13/04/2010



### Marine Transport

Classified as Dangerous Goods by the criteria of the International Maritime Dangerous Goods Code (IMDG Code) for transport by sea; DANGEROUS GOODS.

UN No:	1263
Class-primary:	3 Flammable Liquid
Packing Group:	III
Proper Shipping Name:	PAINT

### Air Transport

Classified as Dangerous Goods by the criteria of the International Air Transport Association (IATA) Dangerous Goods Regulations for transport by air; DANGEROUS GOODS.

UN No:	1263
Packing Group:	III
Proper Shipping Name:	PAINT

## **15. REGULATORY INFORMATION**

Classification:	This material is hazardous according to criteria of Safe Work Australia; HAZARDOUS SUBSTANCE.
Hazard Category:	Xi: Irritant
Risk Phrase(s):	R10: Flammable. R38: Irritating to skin.
Safety Phrase(s):	<ul> <li>S16: Keep away from sources of ignition - No smoking.</li> <li>S24: Avoid contact with skin.</li> <li>S28: After contact with skin, wash immediately with plenty of soap and water.</li> </ul>
Poisons Schedule:	None allocated.

All the constituents of this material are listed on the Australian Inventory of Chemical Substances (AICS).

### **16. OTHER INFORMATION**

Reason(s) for Issue: Change to Transport Information Alignment to HSNO requirements



This safety data sheet has been prepared by SDS Services.

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since DuluxGroup Limited cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material.

If clarification or further information is needed, the user should contact their DuluxGroup representative or DuluxGroup Limited at the contact details on page 1.

DuluxGroup Limited's responsibility for the material as sold is subject to the terms and conditions of sale, a copy of which is available upon request.