The Earthwool® glasswool insulation range of products doesn't look or feel like any insulation you've ever experienced. The natural brown colour represents a level of sustainability and ease of handling never before achieved with Glasswool in New Zealand.

WHY IT'S WORTH THE SWITCH TO LESS ITCH



Soft to handle - easy to install

The super-soft feel of Earthwool® glasswool insulation comes from a revolutionary, patented binder based on rapidly renewable materials.



Non-combustible

Earthwool® glasswool insulation comes with inherent fire performance and will not catch fire.



Absorbs sound

Earthwool® glasswool insulation will absorb sound transfer between rooms and floors.



German innovation - 50 year warranty

The quality of manufacture of Earthwool® glasswool is so good that we offer a full 50 year warranty.



ECOSE® Technology
- no added formaldehyde

Earthwool® glasswool insulation made with ECOSE® Technology benefits from a binder which has no added formaldehyde and is based on renewable, bio-based materials instead of traditional petro-based chemicals.



Sustainable - made using recycled glass

Earthwool® glasswool insulation is made using recycled glass and sand making it a great choice for environmentally conscious customers.



Indoor air comfort

Earthwool® glasswool is certified by Eurofins as an outstanding material according to the VOC (Volatile Organic Compounds) Indoor Air Quality emissions regulations.



More insulation per pack - reduces handling

Unique compression packaging means you can get more insulation per pack and more insulation per load.

CHOOSE YOUR INSULATION SEE OVER





STAY IN YOUR COMFORT ZONE WITH EARTHWOOL® GLASSWOOL INSULATION

Easy to handle, easy to install. We even make it easy to make the right choice.

	MASONRY	A	COUSTIC	PARTITION	J			TIMBE	R FRAME	WALL		
	MASUNKI	STEEL FRAME		TIMBER FRAME		90mm				140mm		
Rating	R-1.5	11kg/m³	11kg/m³	14kg/m³	14kg/m³	R-2.2	R-2.4	R-2.6	R-2.8	R-3.2	R-3.6	R-4.1
Width	600mm	600mm	600mm	580mm	580mm	580mm	580mm	430mm 580mm	430mm 580mm	580mm	580mm	580mm
Comfort Level	SUPERIOR energy saving performance and moisture resistance	BASIC sound absorbing performance for steel frame	ULTIMATE sound absorbing performance for steel frame	SUPERIOR sound absorbing performance for timber frame	ULTIMATE sound absorbing performance for timber frame	BASIC energy saving for the budget conscious home owner	energy so	ERIOR aving and erformance	ULTIMATE sound absorbing performance for timber frame	BASIC thermal performance	SUPERIOR thermal performance	ULTIMATE thermal performance
m²/pack	5.28	32.40	22.68	25.57	16.15	19.51	13.46	6.98 (430) 9.42 (580)	4.99 (430) 6.73 (580)	14.80	10.10	6.10
Thickness	50mm	50mm	75mm	50mm	75mm	90mm	90mm	90mm	90mm	140mm	140mm	140mm
SKU	288885	318555	318562	240991	224657	224623	224626	224629 (430) 224634 (580)	224641 (430) 224644 (580)	224651	296928	296931

			CEILING	SEGMENT			
Rating	R-3.2	R-3.3	R-3.6	R-4.1	R-5.2	R-6.3	
Width	430mm Skillion	430mm	430mm	430mm	430mm	430mm	
Comfort Level	BASIC energy saving performance			ergy saving and sufformance	ULTIMATE energy saving and thermal performance		
Thickness m ² /pack	5.49	10.47	10.47	8.98	5.49	5.49	
Thickness	105mm	155mm	175mm	195mm	210mm	275mm	
SKU	296925	8903532	224589	224592	224597	224602	

CEILING BLANKET				
R-1.8	R-2.9	R-3.2	R-3.6	
1200mm	1200mm	1200mm	1200mm	
BASIC energy saving performance		RIOR energy saving and hermal performance		
16.20	10.20	9.60	8.40	
75mm	115mm	135mm	150mm	
224607	224610	224615	224618	

UNDERFLOOR			
R-1.5	R-1.8		
470mm	500mm 600mm		
SUPERIOR energy saving performance with a wind wash barrier			
19.04	10 (500) 12 (600)		
70mm	75mm		
8911017	327628 (500) 288882 (600)		

QUIETER ALL YEAR ROUND





EECA and RTA compliant products.



