

Deck

SpecRite™



Manufactured For Results.

ENGINEERED HARDWOOD CONCEALED FIX DECKING WITH MERBAU FACE

SELECT GRADE HARDWOOD-KILN DRIED-AS2796.2 2006



- 140mm x 21mm Engineered Hardwood Concealed Fix Decking with premium grade solid merbau face
- Stable, durable and beautiful
- Pre oiled with Feast Watson Industrial Timber Oil for protection against the elements and immediate installation
- Engineered core constructed from premium hardwoods (jambu, northern box and merbau) for gun barrel straight long lengths
- Offers a flawless merbau decking look which is easily laid with concealed fixings
- Aimed at customers who expect the very best in timber performance and visual appeal
- Recommended for use with Ekodeck+ Quickfix 6mm board spacing decking fastening system
- Fasteners sold separately - please consult a Bunnings team member



ENGINEERED HARDWOOD CONCEALED FIX DECKING WITH MERBAU FACE

SELECT GRADE HARDWOOD-KILN DRIED-AS2796.2 2006

Max joist spacing - 450mm centres
Min ground clearance - 400mm
Min distance from side or end to fixed structures - 7mm
Min distance from side edge for fixings - 12mm
Min distance from end for fixings - 12mm

Applications

Decking, fencing, screening and gates

Timber Quality

Select grade in compliance with AS2796.2-2006 and kiln dried for a long-lasting, high-quality appearance.

Fixings

SpecRite Engineered Hardwood Decking is compatible with Ekodeck + Quickfix decking fastening system 6mm board spacing only. **Please note** -the Ekodeck Quickfix 3mm board spacing fixing system is **not** compatible with this SpecRite decking product and must not be used. Please consult a team member at your nearest Bunnings store for assistance.

This product is designed for 'concealed fix' method of installation only. 'Top fix' method of installation should not be used on this product.

Cutting

Tungsten carbide tipped cutting tools and high quality drill bits are recommended for best results. Apply decking oil to cut ends to maximise the life of your deck. Ensure appropriate eye, ear and breathing protection is used when cutting timber.

Ventilation

A minimum ground clearance of 400mm is recommended to allow for adequate ventilation. Additional side and top ventilation is required if the deck is installed with less than 400mm clearance.

Storage

Decking should be stored flat, off the ground and protected from the weather prior to installation.

Finishing

This product has been pre-oiled with Feast Watson Industrial Timber Oil. To prolong the life of your product and maintain its premium look, apply 2 finishing coats of an oil based Feast Watson decking product.

Step 1 - Clean surface with Feast Watson Woodclean
Step 2 - Apply 2 finishing coats of an oil based Feast Watson decking product

Important - To finish with a water-based decking product, prepare timber by first washing with Intergrain PowerPrep followed by cleaning surface with Intergrain Reviva, check surface is ready for coating by performing a water bead test and sprinkling water on the timber. If the water is absorbed into the timber it is ready for coating, then finish with Intergrain UltraDeck.

Warning: The merbau in this product has tannin, a naturally occurring substance which will leach the first few times it is exposed to moisture. A thorough and regular hose down during the first few days will assist with flushing excess tannin away.

Warning: Do not burn off-cuts



Available at
BUNNINGS
warehouse