



# HARD SURFACE PROTECTION

## PLEASE READ THIS IMPORTANT INFORMATION ON GENERAL CONDITIONS FOR APPLICATION AND USE OF HARD SURFACE PROTECTION.

The following information is for any purchaser and/or user of the enclosed product. **Before applying this product you should carefully read these instructions and statements. Failure to comply with the following instructions will void the warranty.**

### Product Information

Hard Surface Protection is a polyethylene film with a pressure sensitive adhesive coating on one side for temporary protection. Product is designed to protect hard surface floors including ceramic, tile, vinyl, marble, formica, fibreglass, factory finished hard floors and laminates from damage during periods of heavy foot traffic associated with renovating, painting, moving, home tours, parties and other high traffic events. This product is also suitable for baths and counter top protection.

**Do not use on refinished, waxed, oiled, unfinished wood or job-site finished flooring. If unsure of finish type, test in an inconspicuous area before use.**

This product should not be utilized on carpeted surfaces. There are other products available for carpeted surfaces.

**THIS PRODUCT SHOULD NOT BE LEFT IN PLACE FOR MORE THAN 30 DAYS. IT IS RECOMMENDED THAT THE MASKING BE MONITORED AND REPLACED MORE FREQUENTLY AND AS NEEDED.** If subjected to direct sunlight, extreme foot traffic, or highly fluctuating temperature conditions, it is recommended that the masking be monitored and replaced more frequently and as needed. The product should not be used outdoors for any reason and voids any liability on the part of the manufacturer.

It is recommended that this product not be stored or attempted to be used in extreme heat conditions (over 35°C), or cold (below 5°C) temperatures.

### Product Application (Test product prior to use)

1. Peel back edge of Hard Surface Protection and begin to unroll. Press down edge at beginning of area to be covered so Hard Surface Protection adheres.
2. Continue unrolling onto hard surface, applying pressure and smoothing down the film while doing so. Do not allow Hard Surface Protection to cover any carpeted areas.
3. Cut end with a sharp edge. When finished, fold edge of the film back against the roll to use at a later time.
4. Removal: roll up Hard Surface Protection and discard.

### Product Use

- For temporary use only – remove or replace with new Hard Surface Protection on 30th day or sooner.
- Perform a suitability test for at least 48 hours to determine suitability.
- Apply only to clean, dry surfaces.
- Apply only to hard non-porous surfaces.
- Do not use on job-site-finished hardwood floors.

### Limited Warranty

Please review product information, instructions, warranty and application info before use.