

• TRUSTED QUALITY SINCE 1921 •

**RUST-OLEUM®****Chalked****ultra matt paint****COASTAL BLUE****DRIES TO A CHALKY SMOOTH FINISH**

easy application ♦ superior coverage

sandable

**340g NET**

**Rust-Oleum® Chalked Ultra Matt Paint** creates an ultra matt finish with superior coverage and adhesion. It transforms and rejuvenates furniture and home décor with a smooth matt finish. Rust-Oleum® Chalked Ultra Matt Paint provides one coat coverage on most surfaces with little to no prep or priming. It can be painted or distressed, giving any project a one-of-a-kind look. Use on wood, metal, ceramic, glass, canvas and more. **TIP:** Some plastics made of polyethylene such as plastic containers are manufactured in a way that may hinder maximum paint adhesion. Test paint in a hidden area first.

READ ALL INSTRUCTIONS BEFORE BEGINNING PROJECT.

**Painting Conditions:** Use outdoors or in a well-ventilated area such as an open garage. Use when temperature is between 10°C and 32°C and humidity is below 65% to ensure proper drying. Avoid spraying in very windy, dusty conditions. Cover surrounding area to protect from spray mist.

**Preparation:** Remove loose paint and rust with a wire brush or sand paper. For superior adhesion, lightly sand glossy or porous surfaces. Remove any wax by lightly wiping surface with mineral turps. Let dry. Clean with soap and water, rinse, and let dry.

**Priming:** Priming is not required for most surfaces. For superior coverage, a Rust-Oleum® primer can be used for surfaces such as treated wood, bare metal and wood. Use a primer when applying a light colour over a dark colour, or to prevent tannin bleed on bare wood.

**Painting:** Shake can vigorously for one minute after mixing ball begins to rattle. Shake often during use. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum®. Hold can upright 25-30cm from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply 2 or more light coats a few minutes apart.

**Dry & Recoat Times:** based on 21°C - 50% relative humidity. Allow more time at cooler temperatures. May recoat within 1 hour or wait after 48 hours. Dries to the touch in 20 minutes and to handle in 1 hour. Fully dry in 24 hours. NOTE: On plastic maximum paint adhesion and durability is achieved in 5-7 days. Chalked clear protective top coat can be applied for added protection. Apply according to instructions on can.

**Clean-up:** Wipe off tip before storing. Clean up wet paint with Xylol or mineral turps. Throw away empty can in trash pickup. Do not burn or place in home trash compactor.

**Clogging:** If valve clogs, twist and pull off spray tip and rinse it in a solvent such as mineral turps. Do not stick pin or other object into the stem.

**Distressing:** This paint can be distressed if desired. To distress, lightly sand the surface with a fine-medium sand paper or a sanding sponge. The more the piece is distressed, the more the original surface will show through. Wait 2 hours before sanding or distressing.

For further application instructions refer to the Technical Data Sheet available at [www.rustoleum.com.au](http://www.rustoleum.com.au) or [www.rustoleum.co.nz](http://www.rustoleum.co.nz) or [www.rustoleum.co.za](http://www.rustoleum.co.za)

**MANUFACTURED BY:** Rust-Oleum Corporation, 11 Hawthorn Parkway, Vernon Hills, Illinois 60061, USA. **IMPORTED AND/OR DISTRIBUTED BY: AUSTRALIA:** Rust-Oleum Australia PTY. LTD. Unit 12, 4 Southridge Street, Eastern Creek, NSW 2766 Australia; P: 1 300 784 476; email: [sales@rustoleum.com.au](mailto:sales@rustoleum.com.au); [www.rustoleum.com.au](http://www.rustoleum.com.au); **NEW ZEALAND:** Rust-Oleum New Zealand, Quad 7 Level 1, 6 Leonard Isitt Drive, Auckland Airport, Auckland 2022 New Zealand; P: 0800 787 865; email: [technical@rustoleum.co.nz](mailto:technical@rustoleum.co.nz); [www.rustoleum.co.nz](http://www.rustoleum.co.nz); **SOUTH AFRICA:** Rust-Oleum South Africa PTY. LTD. PO Box 400 Randvaal 1873 Gauteng, South Africa, P: (016) 365 5120; email: [info@spraymate.co.za](mailto:info@spraymate.co.za); [www.rustoleum.co.za](http://www.rustoleum.co.za)

©2018 Rust-Oleum Corporation Made in the USA 347988 1018

**CAUTION****KEEP OUT OF REACH OF CHILDREN.****READ SAFETY DIRECTIONS BEFORE OPENING OR USING.****FLAMMABLE**

**HAZARD:** Extremely Flammable. Irritation to eyes. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

**SAFETY DIRECTIONS:** DO NOT SWALLOW. Use only in well ventilated areas. Avoid contact with skin, eyes and inhalation of vapour, spray or mist. Wear protective gloves and clothing. Avoid contact with eyes.

**FIRST AID**

**General:** In case of doubt, or when symptoms persist seek medical advice immediately. Never give anything by mouth to an unconscious person.

**Inhalation:** Remove to fresh air. Restore and support continued breathing. Get emergency medical attention. Have trained person give oxygen if necessary. Get medical attention for any breathing difficulty.

**Skin:** Wash thoroughly with water and soap. Remove any contaminated clothing. Wash contaminated clothing before re-use. If irritation occurs consult a physician.

**Eyes:** In case of eye contact, rinse immediately with plenty of water for at least 15 minutes and seek medical advice.

**Ingestion:** If swallowed do NOT induce vomiting. For advice, contact a Poisons Information Centre (Poison Centre Phone: AUS 13 11 26; NZ 0800 764 766; SA 086 155 5777) or a doctor immediately.

For further information refer to the Safety Data Sheet available at [www.rustoleum.com.au](http://www.rustoleum.com.au) or [www.rustoleum.co.nz](http://www.rustoleum.co.nz) or [www.rustoleum.co.za](http://www.rustoleum.co.za)

**PRESSURISED CONTAINER. PROTECT FROM SUNLIGHT AND DO NOT EXPOSE TO TEMPERATURES EXCEEDING 50°C. DO NOT PIERCE OR BURN, EVEN AFTER USE. DO NOT SPRAY ON A NAKED FLAME OR ANY INCANDESCENT MATERIAL. KEEP AWAY FROM SOURCES OF IGNITION - NO SMOKING**

**347790 COASTAL BLUE**

219162

FDB LAYOUT AND TEXT, NOT FOR COLOR MATCH.

Flexible Packaging & Label Specialists  
22790 Heslip  
Novi, Michigan 48375  
800/748-0200 • 248/335-7440  
[www.anchorprinting.com](http://www.anchorprinting.com)

**Specs:**

**Size:** 16 oz 211 x 604  
8.625" x 5.917"

**Coating:** Lamination

**Stock:** White Poly

Please read the proof and specifications carefully. Any errors that are not acknowledged by the customer are NOT the responsibility of Anchor Printing. Customer approval is required for print production.

☐ APPROVED  
OK TO PROCEED

☐ NOT APPROVED  
SEND NEW PROOF

**CUSTOMER INITIALS****Ink Colors**