Material Safety Data Sheet

Page: 1 of

Infosafe No™ HXR76 Issue Date : May 2010 ISSUED by BONDALL

TILEGUARD TILE AND GROUT SEALER Product Name

> Not classified as hazardous according to criteria of NOHSC

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

TILEGUARD TILE AND GROUT SEALER **Product Name**

Product Code 1 litre:63033

BONDALL PTY LTD (ABN 27 008 734 996) Company Name

Address 113 Belmont Avenue

Belmont

WA 6104 Australia

Emergency Tel. 0400 705 773 or Poisons Information Centre: 13 11 26

Tel: (08) 6272 3800 Telephone/Fax Fax: (08) 9277 4068 Recommended Use Tile and Grout Sealant

Other Names Name Product Code

TILE AND GROUT SEALANT

2. HAZARDS IDENTIFICATION

Hazard Not classified as hazardous according to criteria of NOHSC

NON-HAZARDOUS SUBSTANCE. Classification

NON-DANGEROUS GOODS.

Hazard classification according to the criteria of NOHSC.

Dangerous goods classification according to the Australia Dangerous Goods

Risk Phrase(s) Not classified as hazardous according to criteria of NOHSC

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredients	Namo	CAS	Proportion
	Name	CAS	Proporcion
	Water	7732-18-5	up to 100
	Isopropanol	67-63-0	0-<10 %
	Non hazardous water repellant		0-<10 %

4. FIRST AID MEASURES

Inhalation If inhaled, remove affected person from contaminated area. Keep at rest until

recovered. If symptoms persist seek medical attention.

Ingestion Do not induce vomiting. Wash out mouth thoroughly with water. If symptoms

develop seek medical attention.

Skin Wash affected area thoroughly with soap and water. If symptoms develop seek

medical attention.

Eve Irrigate immediately with water for at least 15 minutes until irritation

subsides. If irritation persists, seek medical attention.

First Aid Facilities Eyewash and normal washroom facilities.

Advice to Doctor Treat symptomatically.

5. FIRE FIGHTING MEASURES

Use carbon dioxide, dry chemical, foam, water mist or water spray. Suitable

Extinguishing Media

Under fire conditions this product may emit toxic and/or irritating fumes and Hazards from gases including carbon monoxide and carbon dioxide. Combustion

Products

Specific Hazards Combustible liquid. This product will readily burn under fire conditions.

Precautions in

Fire fighters should wear Self-Contained Breathing Apparatus (SCBA) operated in positive pressure mode and full protective clothing to prevent exposure to connection with Fire

vapours or fumes. Water spray may be used to cool down heat-exposed

containers.

6. ACCIDENTAL RELEASE MEASURES

Print Date: 10/05/2010 CS: 1.4.93

Material Safety Data Sheet

Page: 2 of 4

Infosafe No™ HXR76 Issue Date : May 2010 ISSUED by BONDALL

Product Name TILEGUARD TILE AND GROUT SEALER

Not classified as hazardous according to criteria of NOHSC

Emergency Procedures

Wear appropriate personal protective equipment and clothing to prevent exposure. Extinguish or remove all sources of ignition and stop leak if safe to do so. Increase ventilation. Evacuate all unprotected personnel. If possible contain the spill. Place inert absorbent, non-combustible material onto spillage. Use clean non-sparking tools to collect the material and place into suitable labelled containers for subsequent recycling or disposal. Dispose of waste according to the applicable local and national regulations. If contamination of sewers or waterways occurs inform the local water authorities and EPA in accordance with local regulations.

7. HANDLING AND STORAGE

Precautions for Safe Handling

Use only in a well ventilated area. Keep containers sealed when not in use. Prevent the build up of mists or vapours in the work atmosphere. Avoid inhalation of vapours and mists, and skin or eye contact. Do not use near ignition sources. Do not pressurise, cut, heat or weld containers as they may contain hazardous residues. Maintain high standards of personal hygiene i.e. Washing hands prior to eating, drinking, smoking or using toilet facilities. Store in a cool, dry, well-ventilated area away from sources of ignition, oxidising agents, strong acids, foodstuffs, and clothing. Keep containers closed when not in use and securely sealed and protected against physical damage. Inspect regularly for deficiencies such as damage or leaks. Have appropriate fire extinguishers available in and near the storage area. Take precautions against static electricity discharges. Use proper grounding procedures. For information on the design of the storeroom, reference should be made to Australian Standard AS1940 - The storage and handling of flammable and combustible liquids. Reference should also be made to all applicable local

Conditions for Safe Storage

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

and national regulations.

National Exposure Standards

No exposure value assigned for this specific material by the National Occupational Health and Safety Commission (NOHSC), Australia. However, the available exposure limits for ingredients are listed below:

National Occupational Health And Safety Commission (NOHSC), Australia Exposure Standards:

Substance TWA STEL NOTICES

 ppm
 mg/m³
 ppm
 mg/m³

 Propanol
 400
 983
 500
 1230

TWA (Time Weighted Average): The average airborne concentration of a particular substance when calculated over a normal eight-hour working day, for a five-day week.

STEL (Short Term Exposure Limit): The average airborne concentration over a 15 minute period which should not be exceeded at any time during a normal eight-hour workday.

Biological Limit Values

No biological limit allocated.

Engineering Controls

Provide sufficient ventilation to keep airborne levels below the exposure limits. Where vapours or mists are generated, particularly in enclosed areas, and natural ventilation is inadequate, a flameproof exhaust ventilation system is required. Refer to AS 1940 - The storage and handling of flammable and combustible liquids and AS/NZS 2430.3.1:1997 : Classification of hazardous areas - Examples of area classification - General, for further information concerning ventilation requirements.

Respiratory Protection

If engineering controls are not effective in controlling airborne exposure then an approved respirator with a replaceable mist/vapor filter should be used. Reference should be made to Australian/New Zealand Standards AS/NZS 1715, Selection, Use and Maintenance of Respiratory Protective Devices; and AS/NZS 1716, Respiratory Protective Devices, in order to make any necessary changes for individual circumstances.

Eye Protection

Where there is a risk of spill or splash, Safety glasses with side shields or chemical goggles should be worn. Final choice of appropriate eye/face protection will vary according to individual circumstances. Eye protection devices should conform with Australian/New Zealand Standard AS/NZS 1337 - Eye Protectors for Industrial Applications.

Print Date: 10/05/2010 CS: 1.4.93

3 of Page:

Infosafe No™ HXR76 Issue Date : May 2010 ISSUED by BONDALL

Product Name TILEGUARD TILE AND GROUT SEALER

> according to criteria of NOHSC Not classified as hazardous

Hand Protection Wear gloves of impervious material e.g. PVC / neoprene / nitrile rubber. Final

> choice of appropriate gloves will vary according to individual circumstances i.e. methods of handling or according to risk assessments undertaken. Reference should be made to AS/NZS 2161.1: Occupational protective gloves -Selection, use and maintenance. Avoid prolonged and / or repeated contact with the skin. Use of a water resistant, non-silicone barrier cream is recommended.

> Suitable protective workwear, e.g. cotton overalls buttoned at neck and wrist is recommended. Chemical resistant apron is recommended where large quantities are handled. Industrial clothing should conform to the specifications detailed

in AS/NZS 2919: Industrial clothing.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance Colourless to light yellow liquid

Odour Not available **Boiling Point** 175 - 250°C Solubility in Water Insoluble pH Value Not available 0.05kPa at 20°C Vapour Pressure

0.79 g/mL at 20°C Density

>62°C (PMCC) Flash Point Flammability Combustible >200°C approx. **Auto-Ignition**

Temperature

Body Protection

Not available Flammable Limits -

Lower

Not available Flammable Limits -

Upper

10. STABILITY AND REACTIVITY

Chemical Stability Stable under normal conditions of storage and handling.

Conditions to Avoid Extremes of temperature Strong oxidising agents. Incompatible

Materials

Hazardous

Thermal decomposition may result in the release of toxic and/or irritating

fumes including carbon monoxide and carbon dioxide. Decomposition

Products

Hazardous Will not occur

Polymerization

11. TOXICOLOGICAL INFORMATION

No toxicity data available for this product. The available toxicity data for Toxicology

the ingredients are as follows: Information Acute toxicity data for Propanol:

LD50 (Oral, Rat): 1870 mg/kg LD50 (Dermal, Rabbit): 5040 mg/kg

Inhalation High vapour concentrations may be irritating to the eyes and the respiratory

tract, may cause headaches and dizziness.

Small amounts of liquid aspirated into the respiratory system during ingestion Ingestion

or from vomiting may cause bronchopneumonia or pulmonary oedema.

Skin Frequent or prolonged contact may de-fat and dry the skin, leading to

discomfort and dermatitis.

Eye May be irritating to eyes.

Chronic Effects Not available.

12. ECOLOGICAL INFORMATION

Print Date: 10/05/2010 CS: 1.4.93

Material Safety Data Sheet

Page: 4 of

Infosafe No™ HXR76 Issue Date : May 2010 ISSUED by BONDALL

Product Name TILEGUARD TILE AND GROUT SEALER

Not classified as hazardous according to criteria of NOHSC

Not available **Ecotoxicity** Not available Persistence /

Degradability

Mobility Not available

Environ. Protection Do not discharge this material into waterways, drains and sewers.

13. DISPOSAL CONSIDERATIONS

Dispose of waste according to applicable local and national regulations. Disposal

Considerations

14. TRANSPORT INFORMATION

Not classified as Dangerous Goods according to the Australian Code for the **Transport**

Transport of Dangerous Goods by Road and Rail. (7th edition) Information

15. REGULATORY INFORMATION

Not classified as Hazardous according to criteria of National Occupational Regulatory

Health & Safety Commission (NOHSC), Australia. Information

Not classified as a Scheduled Poison according to the Standard for the Uniform

Scheduling of Drugs and Poisons (SUSDP).

Poisons Schedule Not Scheduled

16. OTHER INFORMATION

MSDS Reviewed: May 2010 Date of preparation or last revision of

MSDS Contact Person/Point MSDS Superseded: August 2004

Chemist: Tel No: (08) 9478 6005

Emergency: Tel No: 0400 705 773 ...End Of MSDS...

© Copyright ACOHS Pty Ltd

Copyright in the source code of the HTML, PDF, XML, XFO and any other electronic files rendered by an Infosafe system for Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd.

Copyright in the layout, presentation and appearance of each Infosafe MSDS displayed is the intellectual property of Acohs Pty Ltd. The compilation of MSDS's displayed is the intellectual property of Acohs Pty Ltd.

Copying of any MSDS displayed is permitted for personal use only and otherwise is not permitted. In particular the MSDS's displayed cannot be copied for the purpose of sale or licence or for inclusion as part of a collection of MSDS without the express written consent of Acohs Pty Ltd.

Print Date: 10/05/2010