SAFETY DATA SHEET

Date of issue/Date of revision 14 December 2020



Section 1. Identification

Product code	: 483200/4L
Product identifier	: J PRO WB INTFLOOR SLIP RES MATT 4L 19
_	
Recommended use and restr	ictions
Use of the substance/ mixture	: Coating.
Uses advised against	: Not applicable.
Supplier's details	: PPG Architectural Coatings 9 Birmingham Ave Villawood, NSW 2163 Australia Tel: +61 2 9794 1200 Fax: + 61 2 9794 1237
Emergency telephone number	: Australia 1800 883 254 / New Zealand 0800 000 096

: Not classified.

Section 2. Hazard(s) identification

Classification of the

substance or mixture		
GHS label elements		
Signal word	1	No signal word.
Hazard statements	1	No known significant effects or critical hazards.
Precautionary statements		
Prevention	1	Not applicable.
Response	1	Not applicable.
Storage	1	Not applicable.
Disposal	1	Not applicable.
Supplemental label elements	:	Not applicable.
Other hazards which do not	:	Prolonged or repeated contact may dry skin and cause irritation. Contains

isothiazolinones. May cause allergic reaction. result in classification Section 3. Composition and ingredient information

Substance/mixture : Mixture

CAS number/other identifiers	
	Not applicable. Mixture.



Product name J PRO WB INTFLOOR SLIP RES MATT 4L 19

Section 3. Composition and ingredient information

Ingredient name	CAS number	% (w/w)
(2-methoxymethylethoxy)propanol	34590-94-8	1 - <10
propane-1,2-diol	57-55-6	1 - <10
2-(2-butoxyethoxy)ethanol	112-34-5	1 - <10

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment or have an OEL and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

SUB codes represent substances without registered CAS Numbers.

Section 4. First aid measures

Description of necessary first aid measures

Eye contact	:	Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.		
Inhalation	-	Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel.		
Skin contact	:	Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners.		
Ingestion	:	If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do NOT induce vomiting.		
Most important symptoms/effects, acute and delayed				
Potential acute health effe	<u>cts</u>			
Eye contact	:	No known significant effects or critical hazards.		
Inhalation	:	No known significant effects or critical hazards.		
Skin contact	:	No known significant effects or critical hazards.		
Ingestion	:	No known significant effects or critical hazards.		
<u>Over-exposure signs/symp</u>	oton	<u>15</u>		
Eye contact	:	No specific data.		
Inhalation	:	No specific data.		
Skin contact	:	No specific data.		
Ingestion	:	No specific data.		
Indication of immediate medical attention and special treatment needed, if necessary				
Notes to physician	:	Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.		
Specific treatments	:	No specific treatment.		
Protection of first-aiders	:	No action shall be taken involving any personal risk or without suitable training.		

See toxicological information (Section 11)

Product name J PRO WB INTFLOOR SLIP RES MATT 4L 19

Section 5. Firefighting measures

Extinguishing media	
Suitable extinguishing media	: Use an extinguishing agent suitable for the surrounding fire.
Unsuitable extinguishing media	: None known.
Specific hazards arising from the chemical	: In a fire or if heated, a pressure increase will occur and the container may burst.
Hazardous thermal decomposition products	: Decomposition products may include the following materials: carbon oxides metal oxide/oxides
Special protective actions for fire-fighters	: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.
Special protective equipment for fire-fighters	 Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.
Hazchem code	: Not applicable.

Section 6. Accidental release measures

Personal precautions, protec	tiv	e equipment and emergency procedures
For non-emergency personnel	:	No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilt material. Put on appropriate personal protective equipment.
For emergency responders	-	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".
Environmental precautions	:	Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).
Methods and material for cor	<u>nta</u>	inment and cleaning up
Small spill	:	Stop leak if without risk. Move containers from spill area. Dilute with water and mop up if water-soluble. Alternatively, or if water-insoluble, absorb with an inert dry material and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.
Large spill	:	Stop leak if without risk. Move containers from spill area. Prevent entry into sewers, water courses, basements or confined areas. Wash spillages into an effluent treatment plant or proceed as follows. Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth

and place in container for disposal according to local regulations (see Section 13). Dispose of via a licensed waste disposal contractor. Note: see Section 1 for

emergency contact information and Section 13 for waste disposal.

Product code 483200/4L

Section 7. Handling and storage

Precautions for safe handling		
Protective measures	:	Put on appropriate personal protective equipment (see Section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas.
Advice on general occupational hygiene	:	Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Remove contaminated clothing and protective equipment before entering eating areas. See also Section 8 for additional information on hygiene measures.
Conditions for safe storage, including any incompatibilities	:	Do not store below the following temperature: 5°C (41°F). Store in accordance with local regulations. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see Section 10) and food and drink. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabelled containers. Use appropriate containment to avoid environmental contamination. See Section 10 for incompatible materials before handling or use.

Section 8. Exposure controls and personal protection

Control parameters	
Occupational exposure limits	
(2-methoxymethylethoxy)propand	bl Safe Work Australia (Australia, 12/2019). Absorbed through skin. TWA: 308 mg/m ³ 8 hours. TWA: 50 ppm 8 hours.
propane-1,2-diol	Safe Work Australia (Australia, 12/2019). TWA: 10 mg/m ³ 8 hours. Form: Particulate TWA: 474 mg/m ³ 8 hours. Form: Vapor and particulates TWA: 150 ppm 8 hours. Form: Vapor and
2-(2-butoxyethoxy)ethanol	particulates ACGIH TLV (United States, 3/2019). TWA: 10 ppm 8 hours. Form: Inhalable fraction and vapor
	Good general ventilation should be sufficient to control worker exposure to airborne contaminants.
For products that are sprayed, whe NZS 4114.	re practicable use a spray booth designed and maintained in accordance with AS/
controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

Individual protection measures

Product code 483200/4L

Product name J PRO WB INTFLOOR SLIP RES MATT 4L 19

Section 8. Exposure controls and personal protection

P	• •
Hygiene measures	: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
Eye/face protection	: Safety glasses with side shields.
Skin protection	
Hand protection	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Gloves	: For prolonged or repeated handling, use the following type of gloves:
	Recommended: Viton®, butyl rubber, nitrile rubber
Body protection	 Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Other skin protection	 Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
Respiratory protection	: Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators. Use a properly fitted, air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.
Restrictions on use	: Not applicable.

References: Eye protectors should conform to AS/NZS 1336 and AS/NZS 1337. Chemical-resistant gloves should conform to AS/NZS 2161.1. Respiratory protection should conform to AS/NZS 1715 and AS/NZS 1716. Occupational footwear should conform to AS/NZS 2210.

Section 9. Physical and chemical properties

Appearance	
Physical state	: Liquid.
Colour	: White.
Odour	: Ethereal.
Odour threshold	: Not available.
рН	
Melting point	: Not available.
Boiling point	: ▶37.78°C (>100°F)
Flash point	: Closed cup: 100°C (212°F) [Product does not sustain combustion.]
Evaporation rate	: Not available.
Flammability (solid, gas)	: Not available.
Lower and upper explosive	: Not available.
(flammable) limits	
Vapour pressure	: Not available.
Vapour density	: Not available.
Relative density	: 1.03
Bulk Density (g/cm ³)	: 1.031

Australia GHS

Page: 6/10

Section 9. Physical and chemical properties

Solubility	: Partially soluble in the following materials: cold water.
Partition coefficient: n- octanol/water	: Not available.
Auto-ignition temperature	: Not available.
Decomposition temperature	: Not available.
Viscosity	: Not Applicable

Section 10. Stability and reactivity

Reactivity	: No specific test data related to reactivity available for this product or its ingredie	ents.
Chemical stability	: The product is stable.	
Possibility of hazardous reactions	: Under normal conditions of storage and use, hazardous reactions will not occu	ır.
Conditions to avoid	: Stable under recommended storage and handling conditions (see Section 7). exposed to high temperatures may produce hazardous decomposition product	
Incompatible materials	: Keep away from the following materials to prevent strong exothermic reactions oxidising agents, strong alkalis, strong acids.	S :
Hazardous decomposition products	: Depending on conditions, decomposition products may include the following materials: carbon oxides metal oxide/oxides	

Section 11. Toxicological information

Information on toxicological effects

Acute toxicity

Product/ingredient name	Result	Species	Dose	Exposure
(2-methoxymethylethoxy) propanol	LC50 Inhalation Vapour	Rat	500 ppm	4 hours
	LD50 Dermal	Rabbit	9.5 g/kg	-
	LD50 Oral	Rat	5.23 g/kg	-
propane-1,2-diol	LD50 Dermal	Rabbit	20800 mg/kg	-
	LD50 Oral	Rat	20 g/kg	-
2-(2-butoxyethoxy)ethanol	LD50 Dermal	Rabbit	2700 mg/kg	-
	LD50 Oral	Rat	4500 mg/kg	-
Conclusion/Summary	: There are no data available	e on the mixture i	tself.	
rritation/Corrosion				
Not available.				
Conclusion/Summary				
Skin	: There are no data available	e on the mixture i	tself.	
Eyes	: There are no data available	e on the mixture i	tself.	
Respiratory	: There are no data available	e on the mixture i	tself.	
Sensitisation				
Not available.				
Conclusion/Summary				
Skin	: There are no data available	e on the mixture i	tself.	

Section 11. Toxicological information

Section 11. Toxico	biogical information
Respiratory <u>Mutagenicity</u> Not available.	: There are no data available on the mixture itself.
Conclusion/Summary Carcinogenicity Not available.	: There are no data available on the mixture itself.
Conclusion/Summary Reproductive toxicity Not available.	: There are no data available on the mixture itself.
Conclusion/Summary <u>Teratogenicity</u> Not available.	: There are no data available on the mixture itself.
Conclusion/Summary Specific target organ toxici Not available.	: There are no data available on the mixture itself. ty (single exposure)
<u>Specific target organ toxici</u> Not available.	<u>ty (repeated exposure)</u>
Aspiration hazard Not available.	
Information on likely routes of exposure	
Potential acute health effects	-
Eye contact	: No known significant effects or critical hazards.
Inhalation	: No known significant effects or critical hazards.
Skin contact	: No known significant effects or critical hazards.
Ingestion	: No known significant effects or critical hazards.
Symptoms related to the phy	vsical, chemical and toxicological characteristics
Eye contact	: No specific data.
Inhalation	No specific data.
Skin contact	No specific data.
Ingestion	: No specific data.
Delayed and immediate effect	cts as well as chronic effects from short and long-term exposure
Conclusion/Summary	: There are no data available on the mixture itself. Contains isothiazolinones. May cause allergic reaction. Exposure to component solvent vapour concentrations in excess of the stated occupational exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme

such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. There is some evidence that repeated exposure to organic solvent vapors in combination with constant loud noise can cause greater

Australia GHS Page: 7/10

Section 11. Toxicological information

		hearing loss than expected from exposure to noise alone. If splashed in the eyes, the liquid may cause irritation and reversible damage. Ingestion may cause nausea, diarrhea and vomiting. This takes into account, where known, delayed and immediate effects and also chronic effects of components from short-term and long- term exposure by oral, inhalation and dermal routes of exposure and eye contact.
<u>Short term exposure</u>		
Potential immediate effects	1	There are no data available on the mixture itself.
Potential delayed effects	1	There are no data available on the mixture itself.
Long term exposure		
Potential immediate effects	1	There are no data available on the mixture itself.
Potential delayed effects	1	There are no data available on the mixture itself.
Potential chronic health effe	ect	<u>s</u>
Not available.		
General	:	No known significant effects or critical hazards.
Carcinogenicity	:	No known significant effects or critical hazards.
Mutagenicity	:	No known significant effects or critical hazards.
Reproductive toxicity	:	No known significant effects or critical hazards.

Numerical measures of toxicity

Acute toxicity estimates

Product/ingredient name	Oral (mg/ kg)	Dermal (mg/kg)	Inhalation (gases) (ppm)	Inhalation (vapours) (mg/l)	Inhalation (dusts and mists) (mg/l)
PRO WB INTFLOOR SLIP RES MATT 4L 19	N/A	106851.2	N/A	1330.1	N/A
(2-methoxymethylethoxy)propanol	5230	9500	N/A	N/A	N/A
propane-1,2-diol	20000	20800	N/A	N/A	N/A
2-(2-butoxyethoxy)ethanol	4500	2700	N/A	N/A	N/A

Section 12. Ecological information

Toxicity

Product/ingredient name	Result	Species	Exposure
(2-methoxymethylethoxy) propanol	Acute EC50 1919 mg/l	Daphnia	48 hours
propane-1,2-diol	Acute LC50 40613 mg/l	Fish	96 hours

Persistence and degradability

Product/ingredient name	Aquatic half-life	Photolysis	Biodegradability
propane-1,2-diol	-	-	Readily

Bioaccumulative potential

Australia GHS	Page: 8/10
---------------	------------

Product name J PRO WB INTFLOOR SLIP RES MATT 4L 19

Section 12. Ecological information

Product/ingredient name	LogPow	BCF	Potential
propane-1,2-diol	-0.92	-	low
2-(2-butoxyethoxy)ethanol	0.56		low

Mobility in soil

Soil/water partition : Not available. coefficient (K_{oc})

Other adverse effects

: No known significant effects or critical hazards.

Section 13. Disposal considerations

Disposal methods The generation of waste should be avoided or minimised wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Empty containers or liners may retain some product residues. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers.

Section 14. Transport information

	ADG	IMDG	ΙΑΤΑ
UN number	Not regulated.	Not regulated.	Not regulated.
UN proper shipping name	-	-	-
Transport hazard class (es)	-	-	-
Packing group	-	-	-
Environmental hazards	No.	No.	No.
Marine pollutant substances	Not applicable.	Not applicable.	Not applicable.

Additional information

ADG	: None identified.
Hazchem code	: Not applicable.
IMDG	: None identified.
ΙΑΤΑ	: None identified.

Product code 483200/4L

Product name J PRO WB INTFLOOR SLIP RES MATT 4L 19

Section 14. Transport information

Special precautions for user : Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

Transport in bulk according : Not applicable. to IMO instruments

Section 15. Regulatory information

Standard for the Uniform Scheduling of Medicines and Poisons		
SUSMP	: Not regulated.	
Model Work Health and Safety Regulations - Scheduled Substances		
No listed substance		
Australia inventory (AICS)	: All components are listed or exempted.	
New Zealand (NZIoC)	: All components are listed or exempted.	

Section 16. Any other relevant information

<u>History</u>	
Date of issue/Date of revision	: 14 December 2020
Date of previous issue	: 11/2/2020
Prepared by	: EHS
Key to abbreviations	: ADG = Australian Dangerous Goods ATE = Acute Toxicity Estimate BCF = Bioconcentration Factor GHS = Globally Harmonized System of Classification and Labelling of Chemicals IATA = International Air Transport Association IBC = International Air Transport Association IBC = International Maritime Dangerous Goods LogPow = logarithm of the octanol/water partition coefficient MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution) NOHSC = National Occupational Health and Safety Commission SUSMP = Standard Uniform Schedule of Medicine and Poisons UN = United Nations
References	: Not available.

Indicates information that has changed from previously issued version.

Notice to reader

The information contained in this data sheet is based on present scientific and technical knowledge. The purpose of this information is to draw attention to the health and safety aspects concerning the products supplied by PPG, and to recommend precautionary measures for the storage and handling of the products. No warranty or guarantee is given in respect of the properties of the products. No liability can be accepted for any failure to observe the precautionary measures described in this data sheet or for any misuse of the products.