



EnduraSeal

Premium Grey Thread Tape

Brand Name: EnduraSeal Premium Grey Thread Tape
Product Description: P.T.F.E. Thread Seal Tape - Gas & Water
Model Number(s): 4920482
Serial Number(s): 6958959327034
Thickness: 0.10mm (+/- 0.015mm)
Length: 8m (+/- 0.5m)
Width: 12mm (+/- 0.5mm)
Density: 1.00g/cm³
Melting Point: 330°C



Gas Usage:

Applicable Standard: AS 4623-2008

Classification: Class III

Rated Working Pressure: 2000 kPa

Working Temperature Range: -10°C to +260°C

Recommended Application: Suitable for use in metallic threaded joints and fittings used in Natural Gas and Liquid Petroleum Gas (LPG) installations.



Gas Safety
Certified
AS 4623-2008
Cert. SAI-400214
SAI Global

Class III 2000kPa
Working Temperature -10°C to +260°C

Potable Water Usage:

Applicable Standard: WMTS-014:2016

Rated Working Pressure: 2000 kPa

Working Temperature Range: 0°C to +80°C

Recommended Application: Suitable for sealing metallic and plastic water pipe threads. WaterMark approved for use with potable water.



WMTS-014:2016
WM74597
ApprovalMark



Application Instructions:

1. Ensure threads are clean and free from oil and dust.
2. Apply the tape to the male thread in the same direction as the thread, using enough tension to ensure that the tape moulds itself to the thread. Applying tape in the opposite direction to the thread may lead to the tape being unwound as the fitting is tightened.
3. For tapered threads, apply a minimum of 4 wraps to the thread. For damaged or non-tapered threads more than 4 wraps may be required.

Product Composition: 99.9% P.T.F.E. Resin. THIS PRODUCT DOES NOT CONTAIN ASBESTOS.

Hazards Identification: Not Classified as Hazardous Goods when used and stored in the correct manner.

When subjected to fire, this product will emit fumes that could be hazardous to health, breathing apparatus and eye protection should be worn in the event of fire involving this product.

Store product in a cool dry place, discard unused product 5 years after purchase date.

Storage:

First Aid Measures:

Inhalation: Unlikely during proper use of product. Keep at rest and seek medical attention if symptoms develop/persist.

Ingestion: Unlikely during proper use of product. Wash out mouth with water, do not induce vomiting. Seek medical attention if symptoms develop/persist.

Skin: Wash affected area with soap and water. If irritation develops seek medical attention.

Eye Contact: Unlikely during proper use of product. Flush eyes with running water until all contaminants have been removed. Seek medical attention if symptoms develop/persist.