

# **SAFETY DATA SHEET**

#### SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

#### **Product Identifier**

Product name Britex Carpet Cleaner Synonyms Not Available

#### Relevant identified uses of the substance or mixture and uses advised against

Not Available

Relevant identified uses

Other means of identification

Carpet Cleaner.

Use according to manufacturer's directions. SDS are intended for use in the workplace. For domestic-use products, refer to consumer labels.

#### Details of the supplier of the safety data sheet

Registered company name	Britex Carpet Care
ABN	80 093 729 787
Address	Unit 10, 25-27 Chapman St Blackburn Nth VIC 3130 AUSTRALIA
Telephone	+61 3 8892 4800
Fax	+61 3 9899 8533
Website	www.britex.com
Email	customerservice@britex.com
Emergency telephone numbers	1800 804 973

#### **SECTION 2 HAZARDS IDENTIFICATION**

# Classification of the substance or mixture

# HAZARDOUS CHEMICAL. NON-DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.

# CHEMWATCH HAZARD RATINGS

	Min	Max	
Flammability	0		
Toxicity	1	1	0 = Minimum
Body Contact	2		1 = Low 2 = Moderate
Reactivity	0		3 = High
Chronic	0		4 = Extreme

Poisons Schedule Not Applicable Classification [1] Skin Corrosion/Irritation Category 2, Serious Eye Damage Category 1, Chronic Aquatic Hazard Category 3 1. Classified by Chemwatch; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI

#### Label elements

Hazard pictogram(s)





SIGNAL WORD DANGER

# Hazard statement(s)

H315 Causes skin irritation. H318 Causes serious eye damage. H412 Harmful to aquatic life with long lasting effects.

#### Precautionary statement(s) Prevention

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P273 Avoid release to the environment.

#### Precautionary statement(s) Response

P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P321	Specific treatment (see advice on this label).
P362	Take off contaminated clothing and wash before reuse.

#### Precautionary statement(s) Storage

Not Applicable

#### Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# **SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

#### Substances

See section below for composition of Mixtures

#### **Mixtures**

CAS No	%[weight]	Name
166736-08-9	1-5	isodecanol propoxylated
61791-26-2	1-5	tallow alkylamine, ethoxylated
103818-93-5	1-5	alcohols C9-11 ethoxylated propoxylated
7732-18-5	>60	water

# **SECTION 4 FIRST AID MEASURES**

# Description of first aid measures

Eye Contact	If this product comes in contact with the eyes:  Immediately hold eyelids apart and flush the eye continuously with running water.  Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.  Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.  Transport to hospital or doctor without delay.  Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	If skin contact occurs: Immediately remove all contaminated clothing, including footwear.  Flush skin and hair with running water (and soap if available).  Seek medical attention in event of irritation.
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>If swallowed do NOT induce vomiting.</li> <li>If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>Observe the patient carefully.</li> <li>Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>Seek medical advice.</li> </ul>

# Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

# **SECTION 5 FIREFIGHTING MEASURES**

# **Extinguishing media**

The product contains a substantial proportion of water, therefore there are no restrictions on the type of extinguishing media which may be used. Choice of extinguishing media should take into account surrounding areas.

Though the material is non-combustible, evaporation of water from the mixture, caused by the heat of nearby fire, may produce floating layers of combustible substances. In such an event consider:

foam.

## Special hazards arising from the substrate or mixture

Fire Incompatibility None known.

# Advice for firefighters

Fire Fighting

Alert Fire Brigade and tell them location and nature of hazard.

Wear breathing apparatus plus protective gloves in the event of a fire. Prevent, by any means available, spillage from entering drains or water courses.

Use fire fighting procedures suitable for surrounding area.

Fire/Explosion Hazard

The emulsion is not combustible under normal conditions. However, it will break down under fire conditions and the hydrocarbon component will burn.

Decomposes on heating and produces toxic fumes of:

carbon dioxide (CO2) nitrogen oxides (NOx)

other pyrolysis products typical of burning organic material.

May emit poisonous fumes.

May emit corrosive fumes.

**HAZCHEM** 

Not Applicable

#### **SECTION 6 ACCIDENTAL RELEASE MEASURES**

#### Personal precautions, protective equipment and emergency procedures

See section 8

#### **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

B41:	٥.	.::::
Minor	અ	2111

**Major Spills** 

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- ▶ Control personal contact with the substance, by using protective equipment.
- ▶ Contain and absorb spill with sand, earth, inert material or vermiculite.

Chemical Class: alcohols and glycols

For release onto land: recommended sorbents listed in order of priority.

SORBENT TYPE	RANK	APPLICATION	COLLECTION	LIMITATIONS
-----------------	------	-------------	------------	-------------

LAND SPILL - SMALL

cross-linked polymer - particulate	1	shovel	shovel	R, W, SS
cross-linked polymer - pillow	1	throw	pitchfork	R, DGC, RT
sorbent clay - particulate	2	shovel	shovel	R,I, P
wood fiber - pillow	3	throw	pitchfork	R, P, DGC, RT
treated wood fiber - pillow	3	throw	pitchfork	DGC, RT
foamed glass - pillow	4	throw	pichfork	R, P, DGC, RT

# LAND SPILL - MEDIUM

cross-linked polymer - particulate	1	blower	skiploader	R,W, SS
polypropylene - particulate	2	blower	skiploader	W, SS, DGC
sorbent clay - particulate	2	blower	skiploader	R, I, W, P, DGC
polypropylene - mat	3	throw	skiploader	DGC, RT
expanded mineral - particulate	3	blower	skiploader	R, I, W, P, DGC
polyurethane - mat	4	throw	skiploader	DGC, RT

# Legend

DGC: Not effective where ground cover is dense

R: Not reusable

I: Not incinerable

P: Effectiveness reduced when rainy

RT:Not effective where terrain is rugged

SS: Not for use within environmentally sensitive sites

W: Effectiveness reduced when windy

Reference: Sorbents for Liquid Hazardous Substance Cleanup and Control;

R.W Melvold et al: Pollution Technology Review No. 150: Noyes Data Corporation 1988

Moderate hazard.

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear breathing apparatus plus protective gloves.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 HANDLING AND STORAGE**

# Precautions for safe handling

DO NOT allow clothing wet with material to stay in contact with skin

Avoid all personal contact, including inhalation.

Wear protective clothing when risk of exposure occurs.

Use in a well-ventilated area.

Prevent concentration in hollows and sumps.

Store in original containers.

Keep containers securely sealed.

Store in a cool, dry, well-ventilated area.

Store away from incompatible materials and foodstuff containers.

#### Conditions for safe storage, including any incompatibilities

Safe handling

Other information

Polyethylene or polypropylene container. **Suitable container** Packing as recommended by manufacturer.

Check all containers are clearly labelled and free from leaks.

Storage incompatibility None known

# **SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION**

# **Control parameters**

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Not Available

#### **Emergency Limits**

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
Britex Carpet Cleaner	Not Available	Not Available	Not Available	Not Available
Ingredient	Original IDLH		Revised IDLH	
isodecanol propoxylated	Not Available		Not Available	
tallow alkylamine, ethoxylated	Not Available		Not Available	
alcohols C9-11 ethoxylated propoxylated	Not Available		Not Available	
water	Not Available		Not Available	

# Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit
isodecanol propoxylated	E	≤ 0.1 ppm
alcohols C9-11 ethoxylated propoxylated	E	≤ 0.1 ppm
Notes:	Occupational exposure banding is a process of assigning chemicals into spadverse health outcomes associated with exposure. The output of this processing of exposure concentrations that are expected to protect worker heal	cess is an occupational exposure band (OEB), which corresponds to a

### MATERIAL DATA

#### Exposure controls

Exposure controls	
Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:  Process controls which involve changing the way a job activity or process is done to reduce the risk.  Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	Safety glasses with side shields.  Chemical goggles.  Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.
Skin protection	See Hand protection below
Hands/feet protection	Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber  NOTE:  The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.  Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance

	and has therefore to be checked prior to the application.		
	The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when		
	making a final choice.		
	Personal hygiene is a key element of effective hand care.		
Body protection	See Other protection below		
	Overalls.		
	Overails.		
Other protection	P.V.C apron.		
	Barrier cream.		
	Skin cleansing		
	cream.		

#### Recommended material(s)

#### **GLOVE SELECTION INDEX**

Glove selection is based on a modified presentation of the:

# "Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the *computer-generated* selection:

Britex Carpet Cleaner

Material	СРІ
BUTYL	Α
NEOPRENE	А
VITON	А
NATURAL RUBBER	С
PVA	С

<sup>\*</sup> CPI - Chemwatch Performance Index

- A: Best Selection
- B: Satisfactory; may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

#### Respiratory protection

Type AK-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Selection of the Class and Type of respirator will depend upon the level of breathing zone contaminant and the chemical nature of the contaminant. Protection Factors (defined as the ratio of contaminant outside and inside the mask) may also be important.

Required minimum protection factor	Maximum gas/vapour concentration present in air p.p.m. (by volume)	Half-face Respirator	Full-Face Respirator
up to 10	1000	AK-AUS / Class1 P2	-
up to 50	1000	-	AK-AUS / Class 1 P2
up to 50	5000	Airline *	-
up to 100	5000	-	AK-2 P2
up to 100	10000	-	AK-3 P2
100+			Airline**

- \* Continuous Flow \*\* Continuous-flow or positive pressure demand A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)
- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

# **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

# Information on basic physical and chemical properties

Appearance	Straw coloured, clear mobile liquid with characteristic odour; miscible with water.		
	· · · · · · · · · · · · · · · · · · ·	·	
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	7.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES**

# Information on basic physical and chemical properties

Appearance	Straw coloured, clear mobile liquid with characteristic odour; miscible with water.		
Physical state	Liquid	Relative density (Water = 1)	Not Available
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	7.5	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Applicable	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Applicable	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Applicable	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Applicable	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 STABILITY AND REACTIVITY**

Reactivity	See section 7
Chemical stability	Unstable in the presence of incompatible materials.  Product is considered stable.  Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

ıformation on toxicological ef	fects		
Inhaled	The material is not thought to produce either adverse health effects or irritation of the respiratory tract following inhalation (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting.  Not normally a hazard due to non-volatile nature of product		
Ingestion	Accidental ingestion of the material may be damaging to t	he health of the individual.	
Skin Contact	following direct contact, and/or produces significant inflam inflammation being present twenty-four hours or more afte repeated exposure; this may result in a form of contact de and swelling (oedema) which may progress to blistering (omay be intercellular oedema of the spongy layer of the sk. The material may accentuate any pre-existing dermatitis of Open cuts, abraded or irritated skin should not be expose	condition d to this material rasions, puncture wounds or lesions, may produce systemic injury with harmful effects.	
Eye	When applied to the eye(s) of animals, the material produ	ces severe ocular lesions which are present twenty-four hours or more after instillation.	
Chronic	Prolonged or repeated skin contact may cause degreasing	g with drying, cracking and dermatitis following.	
	TOXICITY	IRRITATION	
Britex Carpet Cleaner	Not Available	Not Available	
	TOXICITY	IRRITATION	
	Oral (rat) LD50: >2000 mg/kg <sup>[2]</sup>	Eye: moderate to SEVERE*	
isodecanol propoxylated		Skin (rabbit): irritant (OECD 404)*	
		Skin : Moderate	
	TOXICITY	IRRITATION	
tallow alkylamine, ethoxylated	dermal (rat) LD50: >10000 mg/kg <sup>[2]</sup>	Eye(rabbit)(Draize): moderate	
tallow alkylallille, ethoxylated	Oral (rat) LD50: 500 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
llow alkylamine, ethoxylated	dermal (rat) LD50: >10000 mg/kg <sup>[2]</sup>	Eye(rabbit)(Draize): moderate	
	Oral (rat) LD50: 500 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[2]</sup>	Eye (human): SEVERE	
	Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>	Skin: SEVERE	
alcohols C9-11 ethoxylated propoxylated	Oral (rat) LD50: 1378 mg/kg <sup>[2]</sup>		
proposylate	Oral (rat) LD50: 1400 mg/kg <sup>[2]</sup>		
	Oral (rat) LD50: 2700 mg/kg <sup>[2]</sup>		
	TOXICITY	IRRITATION	
water	Oral (rat) LD50: >90000 mg/kg <sup>[2]</sup>	Not Available	

# ISODECANOL PROPOXYLATED

The effects of similar substances have been characterised.

Alkyl amine polyalkoxylates are not acutely toxic by the oral and dermal routes of exposure, or via inhalation under normal use conditions. Concentrated materials are generally corrosive, eye and skin irritants and may be dermal sensitizers. There is no evidence that alkyl amine polyalkoxylates are neurotoxic, mutagenic, or clastogenic.

Surfactants are surface-active materials that can damage the structural integrity of cellular membranes at high dose levels. Thus, surfactants are often corrosive and irritating in concentrated solutions, as indicated by the acute toxicity studies for these inert materials. It is possible that some of the observed toxicity seen in the repeated studies, such as diarrhea or decreased body weight gain, can be attributed to the corrosive and irritating nature of these surfactants.

Generally, lower molecular weight AAPs (lower carbon chain units and less alkoxylation) may potentially be more bioavailable because they may be more easily absorbed and distributed than higher molecular weight compounds. Thus overall, the longer chain carbon amine higher polyalkoxylates should be less bioavailable.

There are no dermal absorption data on the AAPs. However, data on functionally and structurally similar surfactants suggest that dermal absorption of the AAPs is likely to be low.

For Fatty Nitrogen-Derived ether amines and Fatty Nitrogen-derived amines (FND ether amines and FND amines):

FND ether amines and FND amines are very similar in structure and function. The minimal difference among the alkyl substituents and the large database for the FND categories indicates that the structural differences in these large alkyl chains do not result in differences in toxicity or mutagenicity.

The differences in chain length, degree of saturation of the carbon chains, source of the natural oils, or addition of an amino group in the chain would not be expected to have an impact on the toxicity profile. This conclusion is supported by a number of studies in the FND family of chemicals (amines, cationics, and amides as separate categories) that show no differences in the length or degree of saturation of the alkyl substituents and is also supported by the limited toxicity of these long-chain substituted chemicals

The available acute oral LD50 study for the propanamine derivative with the extensive data for the other supporting chemicals provides adequate evidence that the FND ether amines are only moderately to slightly toxic via this route and exposure period.

Polyethers, for example, ethoxylated surfactants and polyethylene glycols, are highly susceptible towards air oxidation as the ether oxygens will stabilize intermediary radicals involved. Investigations of a chemically well-defined alcohol (pentaethylene glycol mono-n-dodecyl ether) ethoxylate, showed that polyethers form complex mixtures of oxidation products when exposed to air.

Sensitization studies in guinea pigs revealed that the pure nonoxidized surfactant itself is nonsensitizing but that many of the investigated oxidation products are sensitizers. Two hydroperoxides were identified in the oxidation mixture, but only one (16-hydroperoxy-3,6,9,12,15-pentaoxaheptacosan-1-ol) was stable enough to be isolated. It was found to be a strong sensitizer in LLNA (local lymph node assay for detection of sensitization capacity).

The material may produce moderate eye irritation leading to inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS.

Tallow derivatives used in the manufacture of cosmetic products such as fatty acids, glycerol, fatty acid esters and soap are regarded as safe if they are obtained by the following minimal processes which must be strictly certified:

- transesterification or hydrolysis at 200°C, under pressure for 20 minutes (glycerol and fatty acids and esters)
- saponification with NaOH 12M (glycerol and soap)
- \* batch process: at 95°C for 3 hours
- \* continuous process: at 140°C, 2 bars for 8 minutes or equivalent.

Moreover, other tallow derivatives (e.g. fatty alcohols, fatty amines, fatty amides) produced from the above mentioned and submitted to further processes are regarded as safe.

Opinion of The Scientific Committee on Cosmetic Products and Non-Food Products intended for Consumers concerning Tallow Derivatives revised and adapted opinion of 24.6.97 adopted by the plenary session of the SCCNFP of 23 September 1998

None of the constituents of tallow were toxic through oral and dermal exposure, they were not ocular or dermal irritants, and they were neither dermal sensitizers nor photosensitizers. The same was true for other oils which contain varying concentrations of the constituents of tallow. Based on the CIR safety evaluations of the individual constituents of tallow and of cosmetic ingredients containing the constituents of tallow, and on the approval of tallow for use in foods and other consumer products, it is concluded that tallow, tallow glyceride, tallow glycerides, hydrogenated tallow glyceride, and hydrogenated tallow glycerides are safe as cosmetic ingredients in the present practices of use Cosmetic Ingredient Review Expert Panel

While it is difficult to generalise about the full range of potential health effects posed by exposure to the many different amine compounds, characterised by those used in the manufacture of polyurethane and polyisocyanurate foams, it is agreed that overexposure to the majority of these materials may cause adverse health effects.

Many amine-based compounds can induce histamine liberation, which, in turn, can trigger allergic and other physiological effects, including bronchoconstriction or bronchial asthma and rhinitis.

Systemic symptoms include headache, nausea, faintness, anxiety, a decrease in blood pressure, tachycardia (rapid heartbeat), itching, erythema (reddening of the skin), urticaria (hives), and facial edema (swelling). Systemic effects (those affecting the body) that are related to the pharmacological action of amines are usually transient.

Typically, there are four routes of possible or potential exposure: inhalation, skin contact, eye contact, and ingestion.

#### Inhalation:

Inhalation of vapors may, depending upon the physical and chemical properties of the specific product and the degree and length of exposure, result in moderate to severe irritation of the tissues of the nose and throat and can irritate the lungs.

Products with higher vapour pressures have a greater potential for higher airborne concentrations. This increases the probability of worker exposure.

Higher concentrations of certain amines can produce severe respiratory irritation, characterised by nasal discharge, coughing, difficulty in breathing, and chest pains.

Chronic exposure via inhalation may cause headache, nausea, vomiting, drowsiness, sore throat, bronchopneumonia, and possible lung damage. Also, repeated and/or prolonged exposure to some amines may result in liver disorders, jaundice, and liver enlargement.

Most undiluted cationic surfactants satisfy the criteria for classification as Harmful (Xn) with R22 and as Irritant (Xi) for skin and eyes with R38 and R41.

#### ALCOHOLS C9-11 ETHOXYLATED PROPOXYLATED

The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.

The material may produce severe skin irritation after prolonged or repeated exposure, and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) thickening of the epidermis.

Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis. Prolonged contact is unlikely, given the severity of response, but repeated exposures may produce severe ulceration. for alcohols C9-11 ethoxylated Somnolence, ataxia, diarrhoea recorded.

# WATER

No significant acute toxicological data identified in literature search.

Alcohol ethoxylates are according to CESIO (2000) classified as Irritant or Harmful depending on the number of EO-units:

EO < 5 gives Irritant (Xi) with R38 (Irritating to skin) and R41 (Risk of serious damage to eyes)

EO > 5-15 gives Harmful (Xn) with R22 (Harmful if swallowed) - R38/41

EO > 15-20 gives Harmful (Xn) with R22-41

>20 EO is not classified (CESIO 2000)

Oxo-AE, C13 EO10 and C13 EO15, are Irritating (Xi) with R36/38 (Irritating to eyes and skin) .

AE are not included in Annex 1 of the list of dangerous substances of the Council Directive 67/548/EEC

ISODECANOL PROPOXYLATED & ALCOHOLS C9-11 ETHOXYLATED PROPOXYLATED

In general, alcohol ethoxylates (AE) are readily absorbed through the skin of guinea pigs and rats and through the gastrointestinal mucosa of rats. AE are quickly eliminated from the body through the urine, faeces, and expired air (CO2). Orally dosed AE was absorbed rapidly and extensively in rats, and more than 75% of the dose was absorbed. When applied to the skin of humans, the doses were absorbed slowly and incompletely (50% absorbed in 72 hours). Half of the absorbed surfactant was excreted promptly in the urine and smaller amounts of AE appeared in the faeces and expired air (CO2)).

Human beings have regular contact with alcohol ethoxylates through a variety of industrial and consumer products such as soaps, detergents, and other cleaning products. Exposure to these chemicals can occur through ingestion, inhalation, or contact with the skin or eyes. Studies of acute toxicity show that volumes well above a reasonable intake level would have to occur to produce any toxic response. Moreover, no fatal case of poisoning with alcohol ethoxylates has ever been reported.

Acute Toxicity	×	Carcinogenicity	×
Skin Irritation/Corrosion	✓	Reproductivity	×
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	×
Respiratory or Skin sensitisation	×	STOT - Repeated Exposure	×
Mutagenicity	×	Aspiration Hazard	×

Legend:

★ - Data either not available or does not fill the criteria for classification

Data available to make classification

# **SECTION 12 ECOLOGICAL INFORMATION**

#### Toxicity

	Endpoint	Test Duration (hr)	Species	Value Source
Britex Carpet Cleaner	Not Available	Not Available	Not Available	Not Not Available Availab
	Endpoint	Test Duration (hr)	Species	Value Source
isodecanol propoxylated	Not Available	Not Available	Not Available	Not Not Available Availab
	Endpoint	Test Duration (hr)	Species	Value Source
tallow alkylamine, ethoxylated	Not Available	Not Available	Not Available	Not Not Available Availab

alcohols C9-11 ethoxylated propoxylated	Endpoint	Test Duration (hr)	Species	Value	Source
	Not Available	Not Available	Not Available	Not Available	Not Available
	Endpoint	Test Duration (hr)	Species	Value	Source
water	Not Available	Not Available	Not Available	Not Available	Not Available
Legend:	V3.12 (QSAR)	, ,	d Substances - Ecotoxicological Information - Aquat tox database - Aquatic Toxicity Data 5. ECETOC Aq ioconcentration Data 8. Vendor Data	•	

Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

DO NOT discharge into sewer or waterways.

#### Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
water	LOW	LOW

# Bioaccumulative potential

Ingredient	Bioaccumulation
water	LOW (LogKOW = -1.38)

#### Mobility in soil

Ingredient	Mobility
water	LOW (KOC = 14.3)

# **SECTION 13 DISPOSAL CONSIDERATIONS**

#### Waste treatment methods

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

Reduction

Reuse

Recyclina

Disposal (if all else fails)

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.

- DO NOT allow wash water from cleaning or process equipment to enter drains. Product / Packaging disposal
  - It may be necessary to collect all wash water for treatment before disposal.
    - In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.

Where in doubt contact the responsible authority.

Recycle wherever possible.

Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.

Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or incineration in a licensed apparatus (after admixture with suitable combustible material).

Decontaminate empty containers.

# **SECTION 14 TRANSPORT INFORMATION**

# Labels Required

Marine Pollutant	NO
HAZCHEM	Not Applicable

Land transport (ADG): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Air transport (ICAO-IATA / DGR): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Sea transport (IMDG-Code / GGVSee): NOT REGULATED FOR TRANSPORT OF DANGEROUS GOODS

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

# **SECTION 15 REGULATORY INFORMATION**

### Safety, health and environmental regulations / legislation specific for the substance or mixture

# isodecanol propoxylated is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

#### tallow alkylamine, ethoxylated is found on the following regulatory lists

Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5

Australian Inventory of Industrial Chemicals (AIIC)

# alcohols C9-11 ethoxylated propoxylated is found on the following regulatory lists

Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals

Australian Inventory of Industrial Chemicals (AIIC)

#### water is found on the following regulatory lists

Australian Inventory of Industrial Chemicals (AIIC)

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	No (isodecanol propoxylated; alcohols C9-11 ethoxylated propoxylated)
Canada - NDSL	No (isodecanol propoxylated; tallow alkylamine, ethoxylated; alcohols C9-11 ethoxylated propoxylated; water)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	No (isodecanol propoxylated; alcohols C9-11 ethoxylated propoxylated)
Japan - ENCS	No (isodecanol propoxylated; tallow alkylamine, ethoxylated; alcohols C9-11 ethoxylated propoxylated)
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	No (isodecanol propoxylated)
USA - TSCA	No (alcohols C9-11 ethoxylated propoxylated)
Taiwan - TCSI	Yes
Mexico - INSQ	No (isodecanol propoxylated; alcohols C9-11 ethoxylated propoxylated)
Vietnam - NCI	Yes
Russia - ARIPS	No (isodecanol propoxylated; alcohols C9-11 ethoxylated propoxylated)
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

# **SECTION 16 OTHER INFORMATION**

Revision Date	10/12/2020
Initial Date	10/12/2020

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

#### Definitions and abbreviations

PC-TWA: Permissible Concentration-Time Weighted Average PC-

 ${\tt STEL: Permissible \ Concentration-Short \ Term \ Exposure \ Limit \ IARC:}$ 

International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists

STEL: Short Term Exposure Limit

TEEL: Temporary Emergency Exposure Limit。

IDLH: Immediately Dangerous to Life or Health Concentrations

OSF: Odour Safety Factor

NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level

TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold

Value

BCF: BioConcentration Factors BEI: Biological Exposure Index

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.

END OF SDS