

Overview of Eurotec adjustable pedestals

Properties/advantages:

- High load-bearing capacity of up to 8 kN/pedestal
- Quick and easy assembly
- Stepless height adjustment
- Resistant to weather, UV exposure, insects and rot

1



Profi-Line adjustable pedestals

- Versatile applications thanks to a modular system comprising four base pedestals of different heights, two rings for increasing the height, and four adapters:
 - **L adapter** for substructures made of aluminium and timber
 - **Click adapter 40** for Eveco aluminium system profile
 - **Click adapter 60** for EVO/EVO Slim aluminium system profile and HKP deck-support profile
 - **Stone adapter** for laying floor slabs
- Basic assembly heights of 3,0 - 16,8 cm
- Height can be increased with extension rings
- High load-bearing capacity of up to 8,0 kN/pedestal

2



Eco-Line adjustable pedestals

- Suitable for substructures made of aluminium and timber
- Four different sizes available
- Assembly heights of 2,5 - 19,8 cm
- Load-bearing capacity of 2,2 kN/pedestal

3



SL PRO adjustable pedestals

- Self-levelling
- UV stability
- High fatigue strength
- Stepless height adjustment from 55 to 102 mm
- Can be combined with the L adapter and Stone adapter
- Can be combined with the +4 and +10 extension rings
- Excellent chemical resistance
- Acoustic damping properties