

# Double Handled Premium Three-Way Tap

## Installation Instructions

Please keep these instructions for future reference and request of replacement parts

# Stefani

### Introduction

Thanks for purchasing this quality Stefani product. This premium 3-way tap is easy to use & install and conveniently delivers filtered or treated water from an installed system. To ensure that it works to its full potential, it needs to be fitted correctly. These fitting instructions have been created to give you all the information you need.

### Supplied Components:

- |  |       |
|--|-------|
| 1. Chrome Plated Brass bodied 3-way tap              | 1 pc  |
| 2. Rubber Gasket, Metal Fixing Gasket & Fixing Screw | 1 set |
| 3. Hose for hot & cold & RO filter water             | 3 pcs |
| 4. Connector piece from hose to ¼" tubing            | 1 pc  |

### Specification

	Min.	Max.
Operating pressure range(bar)	0.2	10
Water temperature	0°C	100°C
Maximum Static Pressure--	10.0 bar	

### Installation

**Step 1:** Direct the flexible hose against the water inlet at the bottom of the tap base and screw it in tightly.

**Step 2:** Install the gasket, O ring, Nut and fix the assembled tap onto the sink or bench area.

**Step 3:** Connect the flexible hose to the three inlet pipes. The connector piece is used to link the filtered water hose to the ¼" tube from the installed system.

**Step 4:** Fully open the taps for maximum water flow and allow the unit to flush through any impurities

**Step 5:** Check all joints and connections for leaks.

### Cleaning & Maintenance

Your fitting has a high-quality finish and should be treated with care to preserve the visible surfaces. All finishes will wear if not cleaned correctly. The only safe way to clean your product is to wipe with a soft damp cloth. Stains can be removed using a washing detergent liquid. All bathroom cleaning products will damage the surface of your fitting, even the non-scratch cleaners.

**NOTE:**-Never use abrasive detergents or disinfectants or those containing alcohol, hydrochloric or phosphoric acid.

### Repair & Maintenance

If the 3 Way Tap begins to drip or show signs of leakage:

1. Turn off the water supply.
2. Remove fitting handle, valve cover and valve.
3. Carefully clean seating and rubber washer.
4. Replace valve, valve cover and handle, and turn on the water supply.

### Customer Service

For installation questions or after sales service, please contact  
Stefani Australasia Pty Ltd ABN 18 054 981 421  
Email: [stefani@stefani.com.au](mailto:stefani@stefani.com.au)  
Phone AUS +61 8 9350 6178  
Phone NZ +64 800 345 711

