



**Timbermate**  
group

# PC Epoxy Putties & Pastes

## Quick Setting PC Epoxy

Waterproof | Non Toxic | Quick Setting



Waterproof



Non toxic when cured



Rapid cure times

(Check individual products for precise times)



Available in both putty and paste for different applications



Mouldable, sandable

## The only waterproof, non toxic, quick-setting PC epoxy putty, now available in Australia

These hand-mouldable, epoxy putty and paste sticks are perfect for quick repairs to a variety of materials.

- Non-toxic when cured
- Just knead and apply or mix the paste
- Waterproof - PC 11 can be used underwater
- Bonds and dries rapidly
- Pastes can be used for bonding, sealing and filling



## Product code & barcode numbers

Product Code	Description	Pack Qty	Barcode
PC7-2	Paste 56G Black	12	9315284530404
PC7-500	Contractor 227G	12	9315284530411
PC11-SYR	Syringe White 28G	12	9315284530428
PC11-2	Paste White 56G	12	9315284530435
PC11-500	Paste White 56G	12	9315284530442
PCCRE	PC Crete 57G	12	9315284530459
PCMAR	PC Marine 57G	12	9315284530480
PCMET	PC Metal 57G	12	9315284530497
PCFAH	PC Fahrenheit 28G	12	9315284530466
PCCLE	PC Clear Epoxy Syringe 28G	12	9315284530510
PCSUPER	PC Super Epoxy 28G	12	9315284530541



FEATURES	PASTES			PUTTIES				LIQUID EPOXY
	PC-7	PC-11	PC-SUPER	PC-METAL	PC-MARINE	PC-CRETE	PC-FAHRENHEIT	PC-CLEAR
WATERPROOF AFTER CURING	•	•	•	•	•	•	•	•
APPLY TO WET SURFACES		•			•	•		
TINTABLE		•						
NO DRIP OR SAG	•	•	•	•	•	•	•	•
SANDABLE	•	•	•	•	•	•	•	•
PAINTABLE	•	•	•	•	•	•	•	•
NSF RATED				•				
FILL CHARACTERISTICS	BEST	EXCELLENT	N/A	GOOD	GOOD	GOOD	GOOD	N/A
STRENGTH	EXCELLENT	EXCELLENT	EXCELLENT	GOOD	GOOD	GOOD	GOOD	EXCELLENT
WORK TIME	1 HR	35 MIN	15 MIN	3 MIN	15 MIN	5 MIN	8 MIN	4 MIN
SERVICE TIME	12-24 HRS	8-15 HRS	3-4 HRS	1 HR	12-24 HRS	12-24 HRS	12-24 HRS	1 HR
HEAT RANGE	-6°C - 93°C	-6°C - 93°C	-29°C - 93°C	-6°C - 120°C	-6°C - 120°C	-6°C - 120°C	-6°C - 260°C	- 29°C - 93°C
TENSILE STRENGTH	2150 PSI	1710 PSI	2650 PSI	900 PSI	700 PSI	650 PSI	700 PSI	2450 PSI
COLOUR	DARK GREY	OFF WHITE	OPAQUE	DARK GREY	WHITE	LIMESTONE	BROWN	CLEAR

## PC Epoxy Putties & Pastes

### PC-7 Heavy Duty Epoxy Paste

- For tough jobs
- Sealing, bonding / shaping
- Filling voids

The strongest and thickest waterproof epoxy paste with great fill characteristics. Can be sanded, painted and also moulded before curing. Dries to a grey colour. Use on dry surfaces only. Non toxic when dry.

Workable time 1 HR  
Dry time 12-24 HRS

PC7-2



### PC-11 Paste Epoxy Paste

- Wet, dry or underwater repairs

The ideal waterproof epoxy paste for wet surfaces or where colour is critical. Cures underwater. Dries to off-white, is tintable and can be sanded. Marine grade.

Also available in syringe pack.  
Non toxic when dry.

Workable time 35 MIN  
Dry time 8-15 HRS

PC11-2



### PC-Clear Epoxy

- For repairs that must be less visible
- Strength rivalling that of heavy duty paste epoxies
- Non yellowing

Fast curing but allows ample time to apply and position the repair.

Workable time 4 MIN  
Dry time 1 HR

PCCLE



### PC-Super Epoxy

- Non-Drip, Translucent Paste
- Strength in excess of 2500 psi

It has unlimited uses in bonding, assembling, filling and sealing most materials and can be applied via a static mix nozzle vertically and overhead. It cures quickly at room temperature to form a resilient, non-conductive bond or seal that resists most chemicals, fresh and salt water, petrol and fuel oil.

Workable time 15 MIN  
Dry time 3-4 HRS

PCSUPER



### PC-Crete Putty

- Fast, emergency repairs to:
  - masonry
  - statues
  - birdbaths
  - steps & curbs
  - anchoring

This waterproof, hand mouldable epoxy is made with real aggregate. Apply to clean, dry surfaces. Non toxic when dry.

Workable time 3 MIN  
Dry time 1 HR

PCCRE



### PC-Marine Putty

Quick emergency repairs to fibreglass, PVC, boats, spas, swimming pools, ponds, water tanks etc.

Hand mouldable, waterproof putty. Quick to cure in wet, dry or underwater conditions. Non toxic when dry.

Workable time 15 MIN  
Dry time 1 HR

PCMAR



### PC-Fahrenheit Putty

- Repairs where temperatures may elevate to 260°C
- Ideal for exhausts, engine blocks, grills, stoves, steam pipes, BBQs etc.

Cures fast, holds strong in high temperatures. Waterproof and non toxic when cured.

Workable time 8 MIN  
Dry time 1 HR

PCFAH



### PC-Metal Putty

- Quick emergency repairs to:
  - gas tanks
  - metal drums
  - radiators
  - metal & steel doors
  - tools
  - pipes etc.

Waterproof liquid steel in a putty! Safe contact with drinking water Ideal for quick repairs to metal. Non toxic when dry.

Workable time 3 MIN  
Dry time 1 HR

PCMET

